


* Channel Compliant for typical CAT6 Channel applications.

Rev.	Description	By	Date

MADE IN USA




Applications

- Gigabit Ethernet 1000 Base-T
- Fast Ethernet 100 Base-T
- Ethernet 10 Base-T
- 4/16 Mbps Token Ring (802.5)
- 100 VG-Any Lan
- 100 Mbps; 55-155-622 Mbps (ATM)
- Voice
- High bandwidth applications
- Applications developed for operation over CAT6 or Class E cabling
- TIA PN-4657 Gigabit Ethernet over CAT6

Standards Compliance and Listings

- UL Listed Components
- Category 6 TIA/EIA-568-B-2.1



Wire Map

Part Number Matrix

P1	Color	P2	CAT6-(LL)-(CC) Replace (LL) with length Replace (CC) with Jacket Color
1	White/Orange	1	JACKET COLOR CODE YE = YELLOW BK = BLACK RD = RED GR = GREEN BL = BLUE GY = GRAY WH = WHITE OR = ORANGE PU = PURPLE
2	Orange	2	
3	White/Green	3	
4	Blue	4	
5	White/Blue	5	
6	Green	6	
7	White/Brown	7	
8	Brown	8	

Item	Description	Qty
1	Cable: CAT6 UTP 24AWG (7/0.196 \pm 0.01mm) x 4P(Bare) PVC	AR
2	Connector: High Performance CAT6 RJ45 Long Body Plug	2



LYNN
 This Drawing is the exclusive property of Lynn Electronics
 Information contained herein may not be disclosed or duplicated
 in any form without the express written consent of Lynn Electronics

Drawing No: **OLG20DXXX-LLL**
 Drawn By: J.Riling
 Drawing Date: 07/15/2008

Desc: CAT6 RJ45/45 Patch Cord, 568B, No Boots
PVC
 Checked By: D.Phillips
 Uncontrolled Copy

Sheet: 1/1
 Unit: FT
 Scale: N/A

UNLESS OTHERWISE SPECIFIED
 DIM. ARE IN INCHES-TOL. ON
 FRACTIONS; DECIMALS: ANGLES:
 $\pm \sim$.XX .01 \pm 1/2
 .XXX005 \pm 1/2
 THIRD ANGLE PROJECTION