



NSI INDUSTRIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING	DETECTION LEVEL
	MIN IN (mm)	MAX IN (mm)										
418-MD	.062 (1.57mm)	.875 (22.225mm)	4.125 (104.775mm)	.042 (1.066mm)	.095 (2.413mm)	.180 (4.572mm)	.150 (3.810mm)	.220 (5.588mm)	18 (80)	V-2	N/A	11598.7
840-MD	.062 (1.57mm)	2.375 (60.325mm)	8.875 (225.425mm)	.049 (1.244mm)	.140 (3.556mm)	.240 (6.096mm)	.175 (4.445mm)	.250 (6.350mm)	40 (178)	V-2	N/A	29628.5
750-MD	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	N/A	24935.3
1150-MD	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	N/A	32007.4
1450-MD	.062 (1.57mm)	4.000 (101.600mm)	14.250 (361.951mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	N/A	32808
14120-MD	.187 (4.75mm)	4.06 (103.1mm)	15.093 (383.362mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	N/A	32778



METAL DETECTABLE CABLE TIES

COLOR DESIGNATIONS:

MD-22 = METAL DETECTABLE, TEAL

MATERIAL:

NYLON 6/6 POLYAMIDE

CONFIDENTIAL PROPERTY OF NSI INDUSTRIES, LLC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF NSI INDUSTRIES, LLC.