



Gas Furnace Limits and Plenum Thermostats

- Direct OEM Replacements
- Economical
- Use 36T Electrical Ratings
120VAC, 3 FLA, 12 LRA, 15A Resistive
240VAC, 1.5 FLA, 6 LRA, 10A Resistive

THERMODISC[®]



MH5304

PART NO.	DESCRIPTION	OPEN °F	CLOSE °F	BOARD WIDTH	BOARD HEIGHT	INSERTION LENGTH
SHL501	L170-40 SPST	170°F	130°F	1.88"	2.8"	3.12"
SHL502	L180-30 SPST	180°F	150°F	1.88"	2.8"	3.12"
SHL503	L190-40 SPST	190°F	150°F	1.88"	2.8"	3.12"
SHL504	L240-40 SPST	240°F	200°F	1.88"	2.8"	3.12"
SHL505	L140-40 SPST	140°F	100°F	1.88"	2.8"	1.87"
SHL506	L170-40 SPST	170°F	130°F	1.88"	2.8"	1.87"
SHL507	L140-30 SPST	140°F	110°F	1.88"	2.8"	3.12"
SHL508	L190-20 SPST	190°F	170°F	1.88"	2.8"	3.12"
SHL509	L240-30 SPST	240°F	210°F	1.88"	2.8"	3.12"
SHL510	L150-20 SPST	150°F	130°F	1.625"	1.44"	3.12"
SHL511	L160-20 SPST	160°F	140°F	1.625"	1.44"	3.12"
SHL512	L170-20 SPST	170°F	150°F	1.625"	1.44"	3.12"
SHL513	L170-40 SPST	170°F	130°F	1.88"	2.94"	3.12"
SHL514	L180-40 SPST	180°F	140°F	1.88"	2.94"	3.12"
SHL515	L200-40 SPST	200°F	160°F	1.88"	2.94"	3.12"
SHL516	L210-40 SPST	210°F	170°F	1.88"	2.94"	3.12"
SHL517	L220-40 SPST	220°F	180°F	1.88"	2.94"	3.12"
SHL518	L250-40 SPST	250°F	210°F	1.88"	2.94"	3.12"
SHL519	L155-30 SPST	155°F	125°F	1.88"	2.8"	7.12"
SHL520	L100-20 SPST	100°F	80°F	1.88"	2.8"	7"
SHL521	L200-20 SPST	200°F	180°F	1.88"	2.8"	7"
SHL522	L160-20 SPST	100°F	140°F	1.88"	2.8"	7"
SHL523	L130-20 SPST	130°F	110°F	1.88"	2.8"	7"
SHL524	L170-20 SPST	170°F	150°F	1.88"	2.8"	7"
SHL525	L180-20 SPST	180°F	160°F	1.88"	2.8"	7"