


REMOVABLE CAP
FOR DUAL ENTRY
(INSERT IN OTHER SIDE)

3/8 INTERNAL
HEX PRESSURE SCREW

REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)

IPLDS750-10 SHOWN



WIRE ENTRY PORT
WIRE RANGE: 750KCMIL - 1/0
PRE-FILLED W/ OXIDE INHIBITOR

NSI PART NUMBER	UL PART NUMBER	NO. OF PORTS	LENGTH
IPLDS750-4	N-IS4G	4	3.55
IPLDS750-6	N-IS6G	6	4.95
IPLDS750-8	N-IS8G	8	6.38
IPLDS750-10	N-IS10G	10	7.80
IPLDS750-12	N-IS12G	12	9.23
IPLDS750-14	N-IS14G	14	10.66
IPLDS750-16	N-IS16G	16	12.09
IPLDS750-20	N-IS20G	20	14.94

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

1. CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
2. UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
3. DUAL RATED FOR 75°C COPPER AND/OR ALUMINUM CONDUCTOR.
4. COLD TEMPERATURE RATED TO -45°C.
5. HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT
6. UV RATED

		POLARIS SALES . CO . INC	
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE: INSULATED STACKED DUAL ENTRY (BOTTOM ROW) 750 CONNECTOR	
NAME DRAWN BY	REVISED 4/30/2024	DWG. NO. IPLDS750-	
MATERIAL: N/A		SCALE: N/A	SHEET: 1 OF 1