

# TurboShearSS



**Work. Perform. Outlast.**  
Limited Lifetime Warranty



Attach to any drill to make fast straight cuts, circles, and squares in heavy asphalt shingles. Shear along a roof valley, or make tight left square cuts and circles to fit around utility outlets, with equal precision and ease. An extra-wide jaw opening with beveled lead-in tip on the upper blade handles multiple shingle layers and a wide, flat lower blade offers exceptional operator control. Heat-treated carbon steel blades with solid carbide inserts hold their edge longer in any life-rated shingle or shingle thickness.



**TSS1**  
Pat. No. 9,649,702



## 360° Rotating Head

The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!

**Capacities:** Layered Asphalt Shingles - 1/2 in. (12.7 mm)



**Drill Requirements:**  
1/4 in. (6.35 mm) Chuck,  
Min. 14.4V - DC, Max 7A-AC

Catalog Number	Description	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSS1	TurboShear, Asphalt Shingles	—	2.3 (1.04)
<b>Replacement Parts</b>			
TSDC	TurboShear Drill Clamp	8 (227)	—
TSCG	TurboShear Chuck Guard	.96 (27)	—
TSS1RB EV	TurboShear Asphalt Shingle Replacement Blades	7.04 (200)	—