

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 19-Nov-2024 Version 1

1. Identification

Product identifier

Product Name 5J-1 INDIAN HEAD GASKET SHELLAC 2 FL.OZ

Other means of identification

Product Code 20539

UN number or ID number UN1866

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW Permatex, Inc.ITW Permatex Canada6875 Parkland Blvd.101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 1

Label elements

Contains ROSIN; METHANOL; METHYL ISOBUTYL KETONE



Danger

Hazard statements

Flammable liquid and vapor.
May cause an allergic skin reaction.
Suspected of causing cancer.
Causes damage to organs.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Contaminated work clothing should not be allowed out of the workplace.

Do not breathe dust.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Use explosion-proof electrical, ventilating and lighting equipment.

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor.

Skin

If skin irritation or rash occurs: Get medical advice and attention.

Wash contaminated clothing before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

3.93 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

28.35 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

97.74 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

93.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

72.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life, Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
ROSIN	8050-09-7	45-70%	-	-
ETHANOL	64-17-5	10-30%	-	-
2-PROPANOL	67-63-0	1-5%	-	-
METHANOL	67-56-1	0.5-1.5%	-	-
METHYL ISOBUTYL KETONE	108-10-1	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. May cause an allergic skin reaction. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use

personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives.

Effects of Exposure Causes damage to organs.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media

Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products

No information available.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ROSIN	TWA: 0.001 mg/m³ total resin	(vacated) TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
8050-09-7	acids inhalable particulate	Formaldehyde	Formaldehyde
	matter	·	
	dermal sensitizer;respiratory		
	sensitizer		
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
2-PROPANOL	TWA: 200 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	STEL: 400 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
METHANOL	TWA: 200 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	STEL: 250 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	Sk*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260 mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 325 mg/m ³
		(vacated) STEL: 325 mg/m ³	
		(vacated) Sk*	
METHYL ISOBUTYL KETONE	TWA: 20 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	STEL: 75 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 205 mg/m ³
		(vacated) TWA: 205 mg/m ³	STEL: 75 ppm
		(vacated) STEL: 75 ppm	STEL: 300 mg/m ³
		(vacated) STEL: 300 mg/m ³	

Chemical name	Alberta	British Columbia	Ontario	Quebec
ROSIN	-	TWA: 0.001 mg/m ³	TWA:	TWA: 0.001 mg/m ³
8050-09-7		Dermal Sensitizer,		TWA:
		Respiratory Sensitizer		
ETHANOL	TWA: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
64-17-5	TWA: 1880 mg/m ³			
2-PROPANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-63-0	TWA: 492 mg/m ³	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm
	STEL: 400 ppm			
	STEL: 984 mg/m ³			
METHANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 262 mg/m ³	STEL: 250 ppm	STEL: 250 ppm	TWA: 262 mg/m ³
	STEL: 250 ppm	Sk*	Sk*	STEL: 250 ppm
	STEL: 328 mg/m ³			STEL: 328 mg/m ³
	Sk*			Skin
METHYL ISOBUTYL KETONE	TWA: 50 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
108-10-1	TWA: 205 mg/m ³	STEL: 75 ppm	STEL: 75 ppm	STEL: 75 ppm

STEL: 75 ppm		
STEL: 307 mg/m ³		

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
ROSIN	TWA: 0.001 mg/m³ Dermal Sensitizer;Respiratory Sensitizer		TWA: 0.001 mg/m³ Dermal Sensitizer; Respiratory Sensitizer	TWA: 0.001 mg/m³ Dermal Sensitizer; Respiratory Sensitizer
ETHANOL	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
2-PROPANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm
METHANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
	STEL: 250 ppm	STEL: 250 ppm	STEL: 250 ppm	STEL: 250 ppm
	Sk*	Sk*	Sk*	Sk*
METHYL ISOBUTYL KETONE	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
	STEL: 75 ppm	STEL: 75 ppm	STEL: 75 ppm	STEL: 75 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
ROSIN		TWA: 0.001 mg/m ³		
ETHANOL	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³
2-PROPANOL	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³ Sk*
METHANOL	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³ Sk*
METHYL ISOBUTYL KETONE	TWA: 50 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m³ STEL: 125 ppm STEL: 510 mg/m³ Sk*

Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL	40 mg/L - urine (Acetone) - end of shift at end of workweek
67-63-0	
METHANOL	15 mg/L - urine (Methanol) - end of shift
67-56-1	
METHYL ISOBUTYL KETONE	1 mg/L - urine (MIBK) - end of shift
108-10-1	

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

Color Brown

Odor No information available
Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
Flammability (solid, gas)

No data available
No data available
No data available

Flammability Limit in Air

Upper flammability limit: 12.7% Lower flammability limit: 2.3% -

Vapor pressure 33 mmHg
Vapor density >1 Air = 1

Relative density 1.02 Water solubility Negligible Solubility(ies) No Data Available **Partition coefficient** No Data Available **Autoignition temperature** No data available **Decomposition temperature** No data available No Data Available Kinematic viscosity Dynamic viscosity No data available

Other information

Explosive properties
Oxidizing properties
No information available

20539 - 5J-1 INDIAN HEAD GASKET SHELLAC 2 FL.OZ

VOC content 28.68%

Density No information available Bulk density No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products Carbon oxides. Aldehydes. Carboxylic acids.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 3,921.70 mg/kg

 ATEmix (dermal)
 2,336.10 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 51.8081 mg/l

 ATEmix (inhalation-dust/mist)
 10.00 mg/l

3.93 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

28.35 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

97.74 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

93.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

72.03 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

F	L.	ΩZ
		~

ROSIN 8050-09-7	= 7600 mg/kg (Rat) = 3000 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
ETHANOL	A3	Group 1	Known	X
64-17-5				
METHYL ISOBUTYL KETONE	A3	Group 2B	-	X
108-10-1				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

No information available. Reproductive toxicity

STOT - single exposure Causes damage to organs.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ROSIN 8050-09-7	EC50: =400mg/L (72h, Desmodesmus subspicatus)	-	-	EC50: 3.8 - 5.4mg/L (48h, Daphnia magna)
ETHANOL 64-17-5	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	Pimephales promelas) LC50: =11130mg/L	-	EC50: =13299mg/L (48h, Daphnia magna)
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE 108-10-1	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Component information	
Chemical name	Partition coefficient
ROSIN	7.7
8050-09-7	
ETHANOL	-0.35
64-17-5	
2-PROPANOL	0.05
67-63-0	
METHANOL	-0.77
67-56-1	
METHYL ISOBUTYL KETONE	1.9
108-10-1	

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local products

regulations. Dispose of waste in accordance with environmental legislation.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld Contaminated packaging

containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

14. Transport information

DOT

UN number or ID number UN1866 Proper shipping name Resin solution

Transport hazard class(es) Packing group Ш **DOT Marine Pollutant**

Marine pollutant ROSIN.

UN1866, Resin solution, 3, III, Marine pollutant Description

127

Special Provisions B1, B52, IB3, T2, TP1

Emergency Response Guide

Number

TDG

UN number or ID number UN1866 UN proper shipping name Resin solution

Transport hazard class(es) Packing group Ш **ROSIN** Marine pollutant name

Description UN1866, Resin solution, 3, III

MEX

UN1866 **UN** number or ID number **UN** proper shipping name Resin solution

Transport hazard class(es) 3 Packing group

Description UN1866, Resin solution, 3, III

Special Provisions 223

ICAO (air)

UN number or ID number ID8000

UN proper shipping name Consumer commodity

Transport hazard class(es) **Special Provisions** A112

IATA

ID8000 **UN** number or ID number

Consumer Commodity **UN proper shipping name**

Transport hazard class(es) **ERG Code** 9L FL.OZ

Special Provisions A112

IMDG

UN number or ID number UN1866 UN proper shipping name Resin solution

Transport hazard class(es) 3
Packing group III
EmS-No. F-E, S-E
Special Provisions 223, 955

Description UN1866, Resin solution, 3, III, (25°C c.c.), Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies **ENCS** Does not comply **IECSC** Complies Complies KECI Complies **PICCS AICS** Complies **NZIoC** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
2-PROPANOL - 67-63-0	1.0	
METHANOL - 67-56-1	1.0	
METHYL ISOBUTYL KETONE - 108-10-1	0.1	

SARA 311/312 Hazard Categories

20539 - 5J-1 INDIAN HEAD GASKET SHELLAC 2 FL.OZ

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHANOL	5000 lb	-	RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	-	RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65	
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)	
METHANOL - 67-56-1	Developmental	
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen	
	Developmental	

^{*}Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ROSIN	-	-	X
8050-09-7			
ETHANOL	X	X	X
64-17-5			
2-PROPANOL	X	X	X
67-63-0			
WATER	-	-	X
7732-18-5			
METHANOL	X	X	X
67-56-1			
METHYL ISOBUTYL KETONE	X	X	X
108-10-1			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 3 Flammability 3 Instability 0 Special hazards - Health hazards 4 * Flammability 3 Physical hazards 0 Personal protection X Chronic Hazard Star Legend *= Chronic Health Hazard*

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:

20539 - 5J-1 INDIAN HEAD GASKET SHELLAC 2 FL.OZ

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision Date 19-Nov-2024

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.