



CEILING TILE PAINT

#20-51 New White, #20-52 Old White

This is a water based paint that covers up and restores stained ceiling tiles to look brand new again. For use on textured and acoustical ceiling tiles. It is fast drying, sprays upright, and will not warp or sag tiles. For easiest application on high ceilings, use Seymour's Spray Wand #Z-606 that is 33 inches long.

Suggested Uses:

Paint acoustic tiles
 Touch up stains on drywall
 Paint crown moldings without removing them

Packaging:

| | |
|--------------------------|--|
| UPC Code | 20-51: 043281001779 20-52: 043281001786 |
| Cans per case | 12 |
| Shipping weight per case | 18 lbs. |
| Container | 20 fluid ounce can |
| Label weight | 16 ounces (454 grams) |
| Shipping Classification | limited quantity, UN 1950 |
| Hazard Class | 2.1 |

Properties:

| | |
|-------------------------|--|
| Coverage | Up to 15 square feet |
| Cleanup | Paint or lacquer thinner |
| Flammability | Flammable |
| Flash point | -4F |
| Specific Gravity | 0.83 |
| Solids Content | 22% |
| MIR value | 0.93, Non-flat coating (cannot exceed 0.95) |
| HAPs content | 16% |
| Storage Temperature | 40-100F |
| Application Temperature | 50-90F |
| Durability | Good |
| Abrasion Resistance | Fair |
| Heat Resistance | 250F |
| Resin System | V.T. Alkyd |
| Shelf life | Guaranteed for 2 years |
| Food contact rating | No |

Dry Time*:

| | |
|----------|------------|
| To touch | 15 minutes |
|----------|------------|

*At 70F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat

*as measured on a 60 degree gloss meter

12-1-2021