

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 30-Dec-2024 Version 1

1. Identification

Product identifier

Product Name PLASTIC, EMBLEM, AND TRIM ADHESIVE

Other means of identification

Product Code 80318

UN number or ID number UN1133

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1

Label elements

Contains N-HEXANE; TOLUENE



Danger

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Do not eat, drink or smoke when using this product.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Use explosion-proof electrical, ventilating and lighting equipment.

Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see supplemental first aid instructions on this label).

Skin

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation occurs: Get medical advice and attention.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

22 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

22 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

29.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor). 92.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful in contact with skin. May be harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Information Review	Date HMIRA filed and date exemption granted (if applicable)
N-HEXANE	110-54-3	60-80%	-	-
TOLUENE	108-88-3	5-10%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin,

eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

Causes damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat,

hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	TWA: 50 ppm;
110-54-3	pSk	TWA: 1800 mg/m ³	TWA: 180 mg/m ³ ;
		(vacated) TWA: 50 ppm	IDLH: 1100 ppm
		(vacated) TWA: 180 mg/m ³	
TOLUENE	TWA: 20 ppm	TWA: 200 ppm	TWA: 100 ppm;
108-88-3	pOt	(vacated) TWA: 100 ppm	TWA: 375 mg/m ³ ;
		(vacated) TWA: 375 mg/m ³	STEL: 150 ppm
		(vacated) STEL: 150 ppm	STEL: 560 mg/m ³
		(vacated) STEL: 560 mg/m ³	IDLH: 500 ppm
		Ceiling: 300 ppm	

Chemical name	Alberta	British Columbia	Ontario	Quebec
N-HEXANE	TWA: 50 ppm;	TWA: 20 ppm;	TWA: 50 ppm;	TWAEV: 50 ppm;
110-54-3	TWA: 176 mg/m³;	Sk	dSk	TWAEV: 176 mg/m ³ ;
	pSk			Sd
TOLUENE	TWA: 50 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWAEV: 20 ppm;
108-88-3	TWA: 188 mg/m³;	Adverse reproductive		
	pSk	effect		

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
N-HEXANE	TWA: 50 ppm; pSk	TWA: 50 ppm; pSk	TWA: 50 ppm; pSk	TWA: 50 ppm; pSk
TOLUENE	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
N-HEXANE	TWA: 50 ppm; STEL: 62.5 ppm; Sk	TWA: 50 ppm;	TWA: 50 ppm; STEL: 62.5 ppm; pSd	TWA: 100 ppm; TWA: 360 mg/m³; STEL: 125 ppm; STEL: 450 mg/m³;
TOLUENE	TWA: 50 ppm; STEL: 60 ppm; Sk	TWA: 20 ppm;	TWA: 50 ppm; STEL: 60 ppm; pSd	TWA: 100 ppm; TWA: 375 mg/m³; STEL: 150 ppm; STEL: 560 mg/m³; Sk

Biological occupational exposure limits

Chemical name	ACGIH
Official flame	Accili

N-HEXANE 110-54-3	0.5 mg/L - urine (2,5-Hexanedione without hydrolysis) - lend of shift
TOLUENE 108-88-3	0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift
	0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant

apron. Wear fire/flame resistant/retardant clothing.

Respiratory protectionUse appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

Color Clear Odor Solvent

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
Flammability (solid, gas)

No data available
No data available
No data available
No data available

Flammability Limit in Air

Upper flammability limit: 7.4%
Lower flammability limit: 1.2%
Vapor pressure 120 mmHg
Vapor density No data available

Relative density 0.73

Water solubility Immiscible in water Solubility(ies) No data available Partition coefficient No data available Autoignition temperature No data available Decomposition temperature No data available Kinematic viscosity No data available Dynamic viscosity No data available

Particle characteristics

Particle Size No data available
Particle Size Distribution No data available

Other information

Explosive properties
Oxidizing properties
No information available

VOC content 80%

DensityNo information availableBulk densityNo information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products Carbon oxides. Nitrogen oxides (NOx). Hydrogen bromide.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be

harmful if inhaled.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness

and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 13,350.50 mg/kg

 ATEmix (dermal)
 3,246.60 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 169.20 mg/l

ATEmix (inhalation-dust/mist) 12.50 mg/l

22 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

22 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

29.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

92.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
N-HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TOLUENE	A4 - Not Classifiable as	Group 3 -	-	-
108-88-3	a Human Carcinogen	Unclassifiable as to		
	-	carcinogenicity in		
		humans		

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not classifiable as to carcinogenicity in humans

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
N-HEXANE	-	LC50: 2.1 - 2.98mg/L	-	-
110-54-3		(96h, Pimephales		
		promelas)		

TOLUENE	EC50: >433mg/L (96h,	LC50: 15.22 -	-	EC50: 5.46 - 9.83mg/L
108-88-3	Pseudokirchneriella	19.05mg/L (96h,		(48h, Daphnia magna)
	subcapitata)	Pimephales promelas)		EC50: =11.5mg/L (48h,
	EC50: =12.5mg/L (72h,	LC50: =12.6mg/L (96h,		Daphnia magna)
	Pseudokirchneriella	Pimephales promelas)		
	subcapitata)	LC50: 5.89 - 7.81mg/L		
	, ,	(96h, Oncorhynchus		
		mykiss)		
		LC50: 14.1 - 17.16mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: =5.8mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: 11.0 - 15.0mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =54mg/L (96h,		
		Oryzias latipes)		
		LC50: =28.2mg/L (96h,		
		Poecilia reticulata)		
		LC50: 50.87 -		
		70.34mg/L (96h,		
		Poecilia reticulata)		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient		
N-HEXANE	4		
110-54-3			
TOLUENE	3.93		
108-88-3			

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

Р

US EPA Waste Number

Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

VN number or ID number
Proper shipping name
Transport hazard class(es)
Packing group
UN1133
Adhesives
3
II

DOT Marine Pollutant

Marine pollutant N-HEXANE.

Description UN1133, Adhesives, 3, II, Limited Quantity

Special Provisions 149, B52, IB2, T4, TP1, TP8

Emergency Response Guide 128

Number

TDG

UN number or ID number UN1133 UN proper shipping name Adhesives Transport hazard class(es) 3

Packing group

Marine pollutant name N-HEXANE

Description UN1133, Adhesives, 3, II

MEX

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group ||

Description UN1133, Adhesives, 3, II

ICAO (air)

UN number or ID number UN1133
UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group | |

Description UN1133, Adhesives, 3, II

Special Provisions A3

<u>IATA</u>

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A3

Description UN1133, Adhesives, 3, II

<u>IMDG</u>

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group II
EmS-No. F-E, S-D

Description UN1133, Adhesives, 3, II, (-26°C c.c.), Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

ENCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
TOLUENE - 108-88-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

_		, , , , , , , , , , , , , , , , , , , ,		
	Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
	N-HEXANE	5000 lb /	-	RQ 5000 lb final RQ
	110-54-3	kg (final RQ)		RQ 2270 kg final RQ
	TOLUENE	1000 lb /	-	RQ 1000 lb final RQ
	108-88-3	1 lb /		RQ 454 kg final RQ
		kg (final RQ)		RQ 1 lb final RQ
		kg (final RQ)		RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65	
N-HEXANE - 110-54-3	Developmental	
TOLUENE - 108-88-3	Developmental	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
N-HEXANE	X	X	X

110-54-3			
TOLUENE	Χ	X	X
108-88-3			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPAHealth hazards2Flammability3Instability0Special hazards-HMISHealth hazards3 *Flammability3Physical hazards0Personal protectionX

Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

United Nations World Health Organization (WHO)

Revision Date 30-Dec-2024

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.