



RUST CONVERTER AND PRIMER #16-45

Seymour's Rust Converter and primer can be applied to any iron or steel surface to penetrate rust and turn it into a protective black coating. This protective coating will be resistant to moisture and prevents future rust growth. Just remove any loose rust, then apply it like a primer to rusted surfaces. Greatly reduces time spent wire brushing and sanding. A topcoat is required for maximum rust protection.

Suggested Uses:

Vehicles
 Trailers
 Fences
 Railings
 Sheet metal
 Storage tanks

Packaging:

UPC Code	043281008693
Cans per case	6
Shipping weight per case	9 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 12 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-2 F
Specific Gravity	0.80
Solids Content	30%
MIR value	0.69, cannot exceed 0.70
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	Yes
Heat Resistance	250 F
Resin System	Chain Stopped Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To recoat/topcoat	24 hours

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

12-1-2021