



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 16-Jan-2025

Version 1

1. Identification

Product identifier

Product Name 84145 BLACK PLASTIC WELDER (ADHESIVE)

Other means of identification

Product Code R478-ADH1

UN number or ID number UN1133

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B

Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

Contains METHYL METHACRYLATE; METHACRYLIC ACID; DIMETHYLBENZYL HYDROPEROXIDE; CUMENE HYDROPEROXIDE; TALC; CUMENE; HYDROQUINONE



Danger

Hazard statements

Highly flammable liquid and vapor.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause cancer.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Do not breathe dust, fume, gas, mist, vapors and spray.
Wash face, hands and any exposed skin thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Use explosion-proof electrical, ventilating, lighting and .? equipment.
Keep cool.

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice and attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Immediately call a POISON CENTER or doctor/physician.
Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

26.24 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
 26.24 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
 94.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
 94.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
 34.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
METHYL METHACRYLATE	80-62-6	45-70%	-	-
METHACRYLIC ACID	79-41-4	5-10%	-	-
DIMETHYLBENZYL HYDROPEROXIDE	80-15-9	1-5%	-	-
BUTYLATED HYDROXY TOLUENE	128-37-0	0.1-1%	-	-
CUMENE HYDROPEROXIDE	80-15-9	0.1-1%	-	-
TALC	14807-96-6	0.1-1%	-	-
CUMENE	98-82-8	0.1-1%	-	-
HYDROQUINONE	123-31-9	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical attention. May cause an allergic skin reaction.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.
Effects of Exposure May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.
Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.
Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Attention! Corrosive material.
Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
METHYL METHACRYLATE 80-62-6	TWA: 50 ppm STEL: 100 ppm dermal sensitizer	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 410 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³
METHACRYLIC ACID 79-41-4	TWA: 20 ppm	(vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m ³ (vacated) Sk*	TWA: 20 ppm TWA: 70 mg/m ³
BUTYLATED HYDROXY TOLUENE 128-37-0	TWA: 2 mg/m ³ inhalable fraction and vapor	(vacated) TWA: 10 mg/m ³	TWA: 10 mg/m ³
TALC 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
CUMENE 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) Sk*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

		Sk*	
HYDROQUINONE 123-31-9	TWA: 1 mg/m ³ dermal sensitizer	TWA: 2 mg/m ³ (vacated) TWA: 2 mg/m ³	IDLH: 50 mg/m ³ Ceiling: 2 mg/m ³ 15 min

Chemical name	Alberta	British Columbia	Ontario	Quebec
METHYL METHACRYLATE 80-62-6	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 100 ppm STEL: 410 mg/m ³	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm
METHACRYLIC ACID 79-41-4	TWA: 20 ppm TWA: 70 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm TWA: 70 mg/m ³
BUTYLATED HYDROXY TOLUENE 128-37-0	TWA: 10 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
TALC 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
CUMENE 98-82-8	TWA: 50 ppm TWA: 246 mg/m ³	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm	TWA: 5 ppm
HYDROQUINONE 123-31-9	TWA: 2 mg/m ³	TWA: 1 mg/m ³ Dermal Sensitizer	TWA: 1 mg/m ³	TWA: 1 mg/m ³

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
METHYL METHACRYLATE	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer
METHACRYLIC ACID	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
BUTYLATED HYDROXY TOLUENE	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
TALC	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
CUMENE	TWA: 5 ppm	TWA: 50 ppm	TWA: 5 ppm	TWA: 5 ppm
HYDROQUINONE	TWA: 1 mg/m ³ Dermal Sensitizer	TWA: 1 mg/m ³	TWA: 1 mg/m ³ Dermal Sensitizer	TWA: 1 mg/m ³ Dermal Sensitizer

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
METHYL METHACRYLATE	TWA: 50 ppm STEL: 100 ppm Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm Sensitizer	TWA: 100 ppm TWA: 410 mg/m ³ STEL: 125 ppm STEL: 510 mg/m ³
METHACRYLIC ACID	TWA: 20 ppm STEL: 30 ppm	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm	
BUTYLATED HYDROXY TOLUENE	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
TALC	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 20 mppcf
CUMENE	TWA: 50 ppm STEL: 74 ppm	TWA: 5 ppm	TWA: 50 ppm STEL: 74 ppm	TWA: 50 ppm TWA: 245 mg/m ³ STEL: 75 ppm STEL: 365 mg/m ³ Sk*
HYDROQUINONE	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 1 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³ STEL: 3 mg/m ³

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles. Face protection shield.
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	No information available
Appearance	No information available
Color	No information available
Odor	No information available
Odor threshold	0.75 ppm

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	10% in deionized water
Melting point / freezing point	No data available	Estimated
Boiling point / boiling range	101 °C / 213.8 °F	
Flash point	12 °C / 53.6 °F	
Evaporation rate	> 1	Butyl acetate = 1
Flammability (solid, gas)	No data available	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. None known
Flammability Limit in Air		
Upper flammability limit:	12.5%	
Lower flammability limit:	1.6%	
Vapor pressure	28 mmHg @ 68°F	
Vapor density	>3	Air = 1
Relative density	0.95	
Water solubility	No data available	Slightly soluble
Solubility(ies)	No Data Available	None known
Partition coefficient	No Data Available	None known
Autoignition temperature	421°C (789.8°F)	
Decomposition temperature	No data available	Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
Kinematic viscosity	No Data Available	Kinematic viscosity at 100 degrees C
Dynamic viscosity	No data available	Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at

which the tested package size will undergo a self-accelerating decomposition reaction.

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	76
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components). Corrosive to the eyes and may cause severe damage including blindness. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.
----------	---

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,810.50 mg/kg
ATEmix (dermal)	3,406.20 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	8.36 mg/l

- 26.24 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 26.24 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 94.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 94.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 34.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE 80-62-6	8420 - 10000 mg/kg (Rat)	5000 - 7500 mg/kg (Rabbit)	= 29.8 mg/L (Rat) 4 h
METHACRYLIC ACID 79-41-4	= 1320 mg/kg (Rat)	500 - 1000 mg/kg (Rabbit)	= 7.1 mg/L (Rat) 4 h
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	= 382 mg/kg (Rat)	= 0.126 mL/kg (Rabbit)	= 220 ppm (Rat) 4 h
BUTYLATED HYDROXY TOLUENE 128-37-0	> 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
CUMENE HYDROPEROXIDE 80-15-9	= 382 mg/kg (Rat)	= 0.126 mL/kg (Rabbit)	= 220 ppm (Rat) 4 h
CUMENE 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
HYDROQUINONE 123-31-9	= 298 mg/kg (Rat)	= 74800 mg/kg (Rabbit)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Skin corrosion/irritation** Classification based on data available for ingredients. Causes severe skin burns and eye damage.
- Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye damage. Causes burns.
- Respiratory or skin sensitization** May cause an allergic skin reaction.
- Germ cell mutagenicity** No information available.
- Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE 80-62-6	-	Group 3	-	-
BUTYLATED HYDROXY TOLUENE 128-37-0	-	Group 3	-	-
TALC 14807-96-6	-	Group 2A	-	X
CUMENE	A3	Group 2B	Reasonably Anticipated	X

98-82-8				
HYDROQUINONE 123-31-9	A3	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
METHYL METHACRYLATE 80-62-6	EC50: =170mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 243 - 275mg/L (96h, Pimephales promelas) LC50: 125.5 - 190.7mg/L (96h, Pimephales promelas) LC50: 170 - 206mg/L (96h, Lepomis macrochirus) LC50: 153.9 - 341.8mg/L (96h, Lepomis macrochirus) LC50: >79mg/L (96h, Oncorhynchus mykiss) LC50: 326.4 - 426.9mg/L (96h, Poecilia reticulata)	-	EC50: =69mg/L (48h, Daphnia magna)
METHACRYLIC ACID 79-41-4	-	LC50: =85mg/L (96h, Oncorhynchus mykiss)	-	-
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	-	LC50: =3.9mg/L (96h, Oncorhynchus mykiss)	-	-
BUTYLATED HYDROXY TOLUENE 128-37-0	EC50: =6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >0.42mg/L (72h, Desmodesmus subspicatus)	-	-	-

CUMENE HYDROPEROXIDE 80-15-9	-	LC50: =3.9mg/L (96h, Oncorhynchus mykiss)	-	-
TALC 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
CUMENE 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata)	-	EC50: =0.6mg/L (48h, Daphnia magna) EC50: 7.9 - 14.1mg/L (48h, Daphnia magna)
HYDROQUINONE 123-31-9	EC50: =0.335mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =0.044mg/L (96h, Oncorhynchus mykiss) LC50: =0.044mg/L (96h, Pimephales promelas) LC50: 0.1 - 0.18mg/L (96h, Pimephales promelas) LC50: =0.17mg/L (96h, Brachydanio rerio)	-	EC50: =0.29mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
METHYL METHACRYLATE 80-62-6	1.38
METHACRYLIC ACID 79-41-4	0.93
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	1.6
BUTYLATED HYDROXY TOLUENE 128-37-0	5.1
CUMENE HYDROPEROXIDE 80-15-9	1.6
CUMENE 98-82-8	3.55
HYDROQUINONE 123-31-9	0.59

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number

Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

UN number or ID number	UN1133
Proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
DOT Marine Pollutant	NP
Description	UN1133, Adhesives, 3, II, Limited Quantity (LQ)
Special Provisions	149, B52, IB2, T4, TP1, TP8
Emergency Response Guide Number	128

TDG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
Description	UN1133, Adhesives, 3, II

MEX

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
Description	UN1133, Adhesives, 3, II

ICAO (air)

UN number or ID number	ID8000
UN proper shipping name	Consumer commodity
Transport hazard class(es)	9
Special Provisions	A112

IATA

UN number or ID number	ID8000
UN proper shipping name	Consumer Commodity
Transport hazard class(es)	9
ERG Code	9L
Special Provisions	A112

IMDG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
EmS-No.	F-E, S-D
Description	UN1133, Adhesives, 3, II, (12°C c.c.), Limited Quantity (LQ)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECI - Korean Existing Chemicals Inventory
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances
- NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
METHYL METHACRYLATE - 80-62-6	1.0
DIMETHYLBENZYL HYDROPEROXIDE - 80-15-9	1.0
CUMENE - 98-82-8	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHYL METHACRYLATE 80-62-6	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ
CUMENE HYDROPEROXIDE 80-15-9	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ
CUMENE 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
HYDROQUINONE 123-31-9	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
CUMENE - 98-82-8	Carcinogen
Cumene - 98-82-8	Carcinogen
Butadiene - 106-99-0	Carcinogen Developmental Female Reproductive Male Reproductive
ETHYL ACRYLATE - 140-88-5	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE 80-62-6	X	X	X
METHACRYLIC ACID 79-41-4	X	X	X
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	X	X	X
BUTYLATED HYDROXY TOLUENE 128-37-0	X	X	X
CUMENE HYDROPEROXIDE 80-15-9	X	X	X
PETROLEUM WAX, UNFINISHED 8002-74-2	X	X	X
TALC 14807-96-6	X	X	X
CUMENE 98-82-8	X	X	X
HYDROQUINONE 123-31-9	X	X	X
Cumene 98-82-8	X	X	X
ACETOPHENONE 98-86-2	X	X	X
Butadiene 106-99-0	X	X	X
ETHYL ACRYLATE 140-88-5	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 3 Flammability 3 Instability 0 Special hazards -
HMIS Health hazards 3* Flammability 3 Physical hazards 0 Personal protection X
Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision Date 16-Jan-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 16-Jan-2025

Version 1

1. Identification

Product identifier

Product Name 84145 BLACK PLASTIC WELDER (ACTIVATOR)

Other means of identification

Product Code R478-ACT-BL2

UN number or ID number UN1133

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Activator

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3

Label elements

Contains METHYL METHACRYLATE; CARBON BLACK



Danger

Hazard statements

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause respiratory irritation.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Contaminated work clothing should not be allowed out of the workplace.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Use explosion-proof electrical, ventilating, lighting and other equipment.
Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.

Skin

If skin irritation or rash occurs: Get medical advice and attention.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower.
Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

19.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
14.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
99.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
99.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
19.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful in contact with skin. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
METHYL METHACRYLATE	80-62-6	65-85%	-	-
CARBON BLACK	1333-86-4	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.
Effects of Exposure	No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
-------------------------------------	---

Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static
---------------------------	---

electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
METHYL METHACRYLATE 80-62-6	TWA: 50 ppm STEL: 100 ppm dermal sensitizer	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 410 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Chemical name	Alberta	British Columbia	Ontario	Quebec
METHYL METHACRYLATE 80-62-6	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 100 ppm STEL: 410 mg/m ³	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
METHYL METHACRYLATE	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer	TWA: 50 ppm STEL: 100 ppm Dermal Sensitizer
CARBON BLACK	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
METHYL METHACRYLATE	TWA: 50 ppm STEL: 100 ppm Sensitizer	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm STEL: 100 ppm Sensitizer	TWA: 100 ppm TWA: 410 mg/m ³ STEL: 125 ppm STEL: 510 mg/m ³
CARBON BLACK	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state

Appearance	No information available
Color	No information available
Odor	No information available
Odor threshold	0.75 ppm

Property

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	10% in deionized water
Melting point / freezing point	No data available	Estimated
Boiling point / boiling range	101 °C / 213.8 °F	
Flash point	12 °C / 53.6 °F	Tag Closed Cup
Evaporation rate	>1	Butyl acetate = 1
Flammability (solid, gas)	No data available	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Flammability Limit in Air		None known
Upper flammability limit:	12.5%	
Lower flammability limit:	1.6%	
Vapor pressure	28 mmHg @ 68°F	
Vapor density	>3	Air = 1
Relative density	0.95	
Water solubility	No data available	Slightly soluble
Solubility(ies)	No Data Available	None known
Partition coefficient	No Data Available	None known
Autoignition temperature	421 °C / 789.8 °F	
Decomposition temperature	No data available	Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Kinematic viscosity **Dynamic viscosity**

No Data Available
No data available

Kinematic viscosity at 100 degrees C
Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	No information available

Density No information available
Bulk density No information available

10. Stability and reactivity

Reactivity No information available.
Chemical stability Stable under normal conditions.
Possibility of hazardous reactions None under normal processing.
Conditions to avoid Heat, flames and sparks.
Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products Carbon oxides. Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 8,472.60 mg/kg
ATEmix (dermal) 4,071.40 mg/kg
ATEmix (inhalation-gas) 99,999.00 ppm
ATEmix (inhalation-vapor) 99,999.00 mg/l
ATEmix (inhalation-dust/mist) 29.9862 mg/l

19.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
14.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
99.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
99.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
19.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE 80-62-6	8420 - 10000 mg/kg (Rat)	5000 - 7500 mg/kg (Rabbit)	= 29.8 mg/L (Rat) 4 h

CARBON BLACK 1333-86-4	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m ³ (Rat) 4 h
---------------------------	-----------------------	-------------------------	-------------------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE 80-62-6	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)**
- A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 - Not Classifiable as to Carcinogenicity in Humans
- Occupational Safety and Health Administration of the US Department of Labor**
- X - Present

Reproductive toxicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
METHYL METHACRYLATE 80-62-6	EC50: =170mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 243 - 275mg/L (96h, Pimephales promelas) LC50: 125.5 - 190.7mg/L (96h, Pimephales promelas) LC50: 170 - 206mg/L (96h, Lepomis)	-	EC50: =69mg/L (48h, Daphnia magna)

		macrochirus) LC50: 153.9 - 341.8mg/L (96h, Lepomis macrochirus) LC50: >79mg/L (96h, Oncorhynchus mykiss) LC50: 326.4 - 426.9mg/L (96h, Poecilia reticulata)		
--	--	---	--	--

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
METHYL METHACRYLATE 80-62-6	1.38

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

UN number or ID number UN1133
Proper shipping name Adhesives
Transport hazard class(es) 3
Packing group II
DOT Marine Pollutant NP
Description UN1133, Adhesives, 3, II, Limited Quantity (LQ)
Special Provisions 149, B52, IB2, T4, TP1, TP8
Emergency Response Guide Number 128

TDG

UN number or ID number UN1133
UN proper shipping name Adhesives
Transport hazard class(es) 3
Packing group II
Description UN1133, Adhesives, 3, II

MEX

UN number or ID number UN1133
UN proper shipping name Adhesives

Transport hazard class(es) 3
 Packing group II
 Description UN1133, Adhesives, 3, II

ICAO (air)

UN number or ID number ID8000
 UN proper shipping name Consumer commodity
 Transport hazard class(es) 9
 Special Provisions A112

IATA

UN number or ID number ID8000
 UN proper shipping name Consumer Commodity
 Transport hazard class(es) 9
 ERG Code 9L
 Special Provisions A112

IMDG

UN number or ID number UN1133
 UN proper shipping name Adhesives
 Transport hazard class(es) 3
 Packing group II
 EmS-No. F-E, S-D
 Description UN1133, Adhesives, 3, II, (12°C c.c.), Limited Quantity (LQ)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing Chemicals Inventory
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances
- NZIoC** - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
METHYL METHACRYLATE - 80-62-6	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHYL METHACRYLATE 80-62-6	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 3	Instability 0	Special hazards -
HMIS	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

- SVHC: Substances of Very High Concern for Authorization:
- PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
- vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
- STOT: Specific Target Organ Toxicity
- ATE: Acute Toxicity Estimate
- LC50: 50% Lethal Concentration
- LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision Date 16-Jan-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.