



IPLD350-5C SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLD350-3C	3	3.52
IPLD350-4C	4	4.57
IPLD350-5C	5	5.62
IPLD350-6C	6	6.67
IPLD350-8C	8	8.77
IPLD350-10C	10	10.87
IPLD350-11C	11	11.92
IPLD350-12C	12	12.97
IPLD350-14C	14	15.07

WIRE ENTRY POINT
WIRE RANGE: 350MCM - #10AWG
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSI FOR SALES @ 800.321.5847



POLARIS
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.

TITLE:

CLEAR INSULATED DUAL ENTRY 350 CONNECTOR

NAME	REVISED
T.MITCHELL	4/17/2024

DWG. NO. IPLD350C SERIES

MATERIAL: N/A

SCALE: N/A

SHEET: 1 OF 1

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT.