


SET SCREW
PLUG SP4

CABLE ENTRY
PLUG CP4

IPLD4-5C SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLD4-3C	3	1.55
IPLD4-4C	4	1.97
IPLD4-5C	5	2.39
IPLD4-6C	6	2.81
IPLD4-8C	8	3.66
IPLD4-10C	10	4.51
IPLD4-12C	12	5.35
IPLD4-14C	14	6.20



WIRE ENTRY PORT
WIRE RANGE: #4 - #14 AWG
PRE-FILLED W/ OXIDE INHIBITOR

1/8" INTERNAL HEX
PRESSURE SCREW



CONTACT NSi FOR SALES @ 800.321.5847

- NOTES:
- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
 - UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
 - DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
 - COLD TEMPERATURE RATED TO -45°C.
 - HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT.



POLARIS
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		<p>TITLE: CLEAR INSULATED DUAL ENTRY #4 CONNECTOR</p>	
DRAWN BY T.MITCHELL		DATE 11/2021	
MATERIAL: N/A		SCALE: N/A	
DWG. NO. IPLD4C SERIES		SHEET: 1 OF 1	