

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

## 1 Identification

|                               |   |  |  |
|-------------------------------|---|--|--|
| Trade name:                   | GLOSS TRUE RED  |  |  |
| Other means of identification |   |  |  |
| Product code:                 | 0000160122  |  |  |
| Recommended use:              | Paint and coatings application.   |  |  |
| Uses advised against:         | Any that differs from the recommended use.  |  |  |
| Manufacturer/Supplier:        | Seymour of Sycamore<br>917 Crosby Avenue<br>Sycamore, IL 60178 USA<br>phone: 815-895-9101<br>www.seymourpaint.com                   |  |  |
| Emergency telephone number:   | 1-800-255-3924  |  |  |
|                               | Seymour of Sycamore<br>3041 Dougall Avenue, Suite 503<br>Windsor, ONT N9E 1S3 CANADA<br>phone: 800-435-4482<br>www.seymourpaint.com |  |  |

## 2 Hazard(s) identification

### Classification of the substance or mixture

|  |           |  |
|--|-----------|--|
| Aerosols 1   | H222-H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |
| Eye irritation 2A                                    | H319      | Causes serious eye irritation.   |
| Specific target organ toxicity (single exposure) 3   | H336      | May cause drowsiness or dizziness.                                       |
| Specific target organ toxicity (repeated exposure) 2 | H373      | May cause damage to organs through prolonged or repeated exposure.       |

### Additional information:

### GHS Hazard pictograms



GHS02 GHS07 GHS08

### Signal word

Danger

### Hazard-determining components of labeling:

Acetone

methyl isobutyl ketone

Extremely flammable aerosol. Pressurized container: may burst if heated.  
Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

### Effects of chronic overexposure:

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

### Classification according to (d)(1)(ii) of § 1910.1200

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

### Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

|          |                        |        |
|----------|------------------------|--------|
| 67-64-1  | Acetone                | 25-50% |
| 74-98-6  | propane                | 15-25% |
| 110-19-0 | Isobutyl Acetate       | 10-15% |
| 106-97-8 | n-butane               | 5-10%  |
| 108-65-6 | PM acetate             | 1-5%   |
| 108-10-1 | methyl isobutyl ketone | 1-5%   |
| 107-87-9 | Methyl Propyl Ketone   | 1-5%   |

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: GLOSS TRUE RED**

2807-30-9 Glycol Ether EP

(Contd. of page 1)

1-5%

**4 First-aid measures****Description of first aid measures****After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:**

Dizziness

**Indication of any immediate medical attention needed:**

No further relevant information available.

**5 Fire-fighting measures****Extinguishing media**

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

**Extinguishing agents:**

Can form explosive gas-air mixtures.

**Special hazards:**

A respiratory protective device may be necessary.

**Protective equipment for firefighters:**

Cool endangered receptacles with water spray.

**Additional information****6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

**Environmental precautions:**

Do not allow product to reach sewage systems or ground water.

**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Fire/explosion protection:**

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

**Conditions for safe storage:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

**67-64-1 Acetone**

|     |  |
|-----|--|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm   |
| TLV | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm |
|     | Long-term value: 594 mg/m <sup>3</sup> , 250 ppm   |

A4, BEI

**74-98-6 propane**

|     |  |
|-----|--|
| PEL | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV | see Appendix F Minimal oxygen content ( D, EX)     |

**110-19-0 Isobutyl Acetate**

|     |   |
|-----|---|
| PEL | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm  |
| REL | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm  |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm |
|     | Long-term value: 238 mg/m <sup>3</sup> , 50 ppm   |

**106-97-8 n-butane**

|     |  |
|-----|--|
| REL | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm        |
| TLV | Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm (EX) |

**108-65-6 PM acetate**

|      |                         |
|------|-------------------------|
| WEEL | Long-term value: 50 ppm |
|------|-------------------------|

(Contd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: GLOSS TRUE RED**

(Contd. of page 2)

**108-10-1 methyl isobutyl ketone**

|     |  |
|-----|--|
| PEL | Long-term value: 410 mg/m <sup>3</sup> , 100 ppm |
| REL | Short-term value: 300 mg/m <sup>3</sup> , 75 ppm |
|     | Long-term value: 205 mg/m <sup>3</sup> , 50 ppm  |
| TLV | Short-term value: 307 mg/m <sup>3</sup> , 75 ppm |
|     | Long-term value: 82 mg/m <sup>3</sup> , 20 ppm   |
|     | BEI, A3  |

**107-87-9 Methyl Propyl Ketone**

|     |   |
|-----|---|
| PEL | Long-term value: 700 mg/m <sup>3</sup> , 200 ppm  |
| REL | Long-term value: 530 mg/m <sup>3</sup> , 150 ppm  |
| TLV | Short-term value: 529 mg/m <sup>3</sup> , 150 ppm |

**Ingredients with biological limit values:****67-64-1 Acetone**

|     |  |
|-----|--|
| BEI | 25 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
|-----|--|

**108-10-1 methyl isobutyl ketone**

|     |  |
|-----|--|
| BEI | 1 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MIBK |
|-----|--|

**Exposure controls****Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.

Wash hands after use.

**Breathing equipment:**

Do not eat or drink while working.  
A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****General Information:****Physical state**

Aerosol

**Odor:**

Aromatic

**Odor threshold:**

Not determined.

**Melting point/Melting range**

Undetermined.

**Boiling point:**

-44 °C (-47.2 °F)

**Flammability:**

Extremely flammable.

**Lower Explosion Limit:**

1.7 Vol %

**Upper Explosion Limit:**

10.9 Vol %

**Flash point:**

-19 °C (-2.2 °F)

**Decomposition temperature:**

Not determined.

**pH-value:**

Not determined.

**Viscosity:**

Not determined.

**Kinematic:**

Not determined.

**Dynamic:**

Not determined.

**Solubility:**

Not determined.

**Vapor pressure:**

40 PSI 2750 hPa

**Vapor Pressure:**

40 PSI, 2750 hPa

**Relative Density:**

Between 0.77 and 0.85 (Water equals 1.00)

**Vapor density**

Not determined.

**Particle characteristics**

Not applicable.

**Appearance:**

Aerosol.

**Ignition temperature:**

Product is not self-igniting.

**Danger of explosion:**

Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

**Water:**

0.0 %

**Evaporation rate**

Not applicable.

**Partition coefficient: n-octanol/water:**

Not determined.

**10 Stability and reactivity****Conditions to avoid:**

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Possibility of hazardous reactions:**

No dangerous reactions known.

**Conditions to avoid**

No further relevant information available.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name:** GLOSS TRUE RED

(Contd. of page 3)

**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

**LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

Oral LD50 4,763 mg/kg (rabbit)

**108-65-6 PM acetate**Oral LD50 8,500 mg/kg (rat)  
Inhalative LC50/4 h 35.7 mg/l (rat)**108-10-1 methyl isobutyl ketone**Oral LD50 2,100 mg/kg (rat)  
Dermal LD50 16,000 mg/kg (rab)  
Inhalative LC50/4 h 11 mg/l (ATE)  
8.3-16.6 mg/l (rat)**Skin effects:** No irritant effect.**Eye effects:** Irritating effect.**Sensitization:** No sensitizing effects known.**Aspiration hazard****Interactive effects** No interactive effects between components are known.**IARC (International Agency for Research on Cancer)**

108-10-1 methyl isobutyl ketone

2B

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**Alternative sources for toxicological information**

No non-standard sources for toxicological information where used.

## 12 Ecological information

**Toxicity****Aquatic toxicity:****Persistence and degradability:****Other information:**

Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

**Bioaccumulative potential:****Mobility in soil:****Results of PBT and vPvB assessment****PBT:****vPvB:****Other adverse effects:**

No further relevant information available.

No further relevant information available.

No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Waste treatment methods****Recommendation:**

Completely empty cans should be recycled.

**Recommended cleansing agent:**

Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number**

UN1950

**DOT**

UN1950

UN1950

**UN proper shipping name:**

AEROSOLS, flammable

**DOT**

AEROSOLS, flammable

**Transport hazard class(es):**

2.1 Gases

**Class**

No

**Marine pollutant:**

--

**DOT**

--

**Packaging Group:**

Warning: Gases

**Special precautions for user:**

F-D,S-U

**EMS Number:**

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GLOSS TRUE RED

(Contd. of page 4)

## 15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Toxic Substances Control Act

(TSCA):

Consumer Product Safety

Commission (CPSC):

All ingredients are found on the inventory list of substances.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### Hazardous Air Pollutants

|           |                              |
|-----------|------------------------------|
| 108-10-1  | methyl isobutyl ketone       |
| 1330-20-7 | xylene (mix)                 |
| 100-41-4  | ethyl benzene                |
| 136-52-7  | cobalt bis(2-ethylhexanoate) |

### California Proposition 65 chemicals known to cause cancer:

|          |                        |
|----------|------------------------|
| 108-10-1 | methyl isobutyl ketone |
| 100-41-4 | ethyl benzene          |

### Prop 65 chemicals known to cause birth defects or reproductive harm:

|          |                        |
|----------|------------------------|
| 108-10-1 | methyl isobutyl ketone |
|----------|------------------------|

### CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

### EPA:

|          |                        |   |
|----------|------------------------|---|
| 67-64-1  | Acetone                | I |
| 110-19-0 | Isobutyl Acetate       | D |
| 108-10-1 | methyl isobutyl ketone | I |

### GHS label elements

### Precautionary statements

The product is classified and labeled according to the Globally Harmonized System (GHS).  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

## 16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Contact:

Regulatory Affairs

Date of previous version

05/20/2025

Date of preparation

01/13/2026

### Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EPA: Environmental Protection Agency

IARC: International Agency for the Research of Cancer

NIOSH: National Institute for Occupational Safety and Health

TSCA: Toxic Substances Control Act

CPSC: Consumer Product Safety Commission

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Aerosols 1: Aerosols – Category 1

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3

Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2