

FEATURES:

1. Made from tin-plated aluminum.
2. UL-486B listed for aluminum and copper conductor combinations (Dual Rated).

POLARIS®

PROGRAM:	SOLIDWORKS
UPDATED:	10/2024
SALES REV:	A
SIZE:	B (11x17)

MECHANICAL CONNECTORS: APS - SERIES ALUMINUM, DUAL RATED SPLIT BOLTS

CAT. NO.	RANGE OF EQUAL MAIN AND TAP (COPPER AND ALUMINUM)	WIRE DIAMETER RANGE (IN.)	RECOMMENDED TORQUE (IN. LB.)	STD. CTN. QTY.
APS06	10 SOL. – 6 STR	0.101 – 0.184	165	100
APS04	10 SOL. – 4 STR	0.101 – 0.232	165	75
APS02	8 STR. – 2 STR	0.146 – 0.292	275	40
APS11	8 SOL. – 1/0 STR	0.162 – 0.375	385	20
APS21	2 SOL. – 2/0 STR	0.257 – 0.418	390	15
APS41	6 STR. – 4/0 STR	0.368 – 0.575	650	6
APS350 (Not CSA)	2/0 STR. – 350 MCM	0.414 – 0.681	650	3
APS500	3/0 STR. – 500 MCM	0.464 – 0.814	825	2

SPECIFICATIONS:

- UL486A/B Listed Wire Connector.

