

Can

Photo

Not

Available

## STAINLESS STEEL

# 5-54

Stainless Steel contains 316L stainless steel pigment to provide a durable finish that prevents rust while resisting the effects of corrosion, sunlight, and chemicals. Very effective in harsh seacoast and industrial environments. Dries quickly to a satin finish and is non-yellowing.

---

### Suggested Uses:

Protect metal  
Touch up appliances  
Paint metal structures  
Touch up welds

---

### Packaging:

UPC Code	043281003469
Container	5 GALLON CAN (18.9 LITERS)
Shipping Classification	limited quantity, UN 1263
Hazard Class	3
Flammability	WARNING! Flammable liquid and vapor.

---

### Properties:

Coverage	Up to 300 square feet/gal.
Cleanup	Paint/lacquer thinner
Flash point	4F
Solids Content	46%
VOC content	368 g/L
HAPS Content	4%
Viscosity	35-45 on a #4 Ford cup
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Acrylic lacquer
Density	8.8 pounds per gallon
Shelf life	1 year
Food contact rating	Category 21: Acceptable for incidental food contact.

### Dry Time\*:

To touch	15 minutes
To recoat	anytime

\*At 72F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with  
multiple coats and excessively thick coats\*\*

**Gloss\*:** 25-35

\*as measured on a 60 degree gloss meter

12-2-2021