Printing date 01/24/2024 Revised On 01/24/2024

## 1 Identification of the substance and manufacturer

Trade name: **HEAVY DUTY ANTI SEIZE** 

0006201507 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com www.seymourpaint.com

Seymour of Sycamore

**Emergency telephone number:** 

1-800-255-3924

## 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. Skin Irritation 2 Eye Irritation 2A H319 Causes serious eye irritation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Single Exposure 3

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation. Causes serious eye irritation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.

Specific treatment (see on thiś label).

Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

# 3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:** 

			·····   -·······	
Dangerous components:				
	616-38-6	dimethyl carbonate		15-25%
	74-98-6	propane		15-25%
		Acetone		≥5-<10%
	106-97-8			5-10%
	108-88-3			≥5-<10%
	110-54-3			≥1-<5%
64	4742-89-8	VM&P Naphtha		1-5%

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. After skin contact: After eye contact:

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/24/2024 Revised On 01/24/2024

Trade name: HEAVY DUTY ANTI SEIZE

After swallowing: Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

## 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace
---

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV (USA) Short-term value: 500 ppm

Long-term value: 250 ppm A4, BEI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm \*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, OTO, A4

110-54-3 hexane

PEL (USA) Long-term value: 1800 mg/m³, 500 ppm

REL (USA) Long-term value: 180 mg/m<sup>3</sup>, 50 ppm

TLV (USA) Long-term value: 50 ppm

Skin; BEI

Mineral Oil

PEL (USA) Long-term value: 5 mg/m<sup>3</sup>

REL (USA) Short-term value: 10 mg/m³

Long-term value: 5 mg/m<sup>3</sup>

oil mist

TLV (USA)

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/24/2024 Revised On 01/24/2024

#### Trade name: HEAVY DUTY ANTI SEIZE

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

110-54-3 hexane

BEI (USA) 0.5 mg/L

Medium: urine Time: end of shift

Parameter: 2.5-Hexanedione without hydrolysis

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Nitrile gloves. Hand protection:

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

#### 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. Not determined. pH-value: Melting point/Melting range Undetermined. Boiling point: -110 °C (-166 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

**Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture. 1.7 Vol %

Lower Explosion Limit: **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

0.0 % Water:

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 4)

Ш

Printing date 01/24/2024 Revised On 01/24/2024

Trade name: HEAVY DUTY ANTI SEIZE

Incompatible materials: No further relevant information available. (Contd. of page 3)

Hazardous decomposition: No dangerous decomposition products known.

# 11 Toxicological information

LD/LC50 values that are relevant for classification:

616-38-6 dimethyl carbonate Oral LD50 13,000 mg/kg (rat)

Information on toxicological effects: No data available. No irritant effect. Skin effects: No irritating effect. Eye effects:

Sensitization: No sensitizing effects known.

#### 12 Ecological information

Aguatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons Other information:

(HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Remark: Harmful to fish

Other adverse effects: No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation: Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number** UN1950 DOT UN1950 UN1950

Aerosols, flammable DOT

Transport hazard class(es):

2.1 Gases Class Marine pollutant: No

Warning: Gases Special precautions for user:

**EMS Number:** F-D,S-Ŭ

Packaging Group:

**UN "Model Regulation":** UN1950, Aerosols, 2.1

## 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

110-54-3 hexane

**Toxic Substances Control Act** 

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety Comission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

110-54-3 hexane

EPA:

67-64-1 Acetone 110-54-3 hexane

16 Other information

Contact: Regulatory Affairs