BRIDGEPORT®

# RAINTIGHT COMPRESSION CONNECTORS

## CONQUER ANY ENVIRONMENT



NSI

BRIDGEPORT



250-RT2XL

## RT2XL MIGHTY SEAL™ EMT CONNECTORS

Compression style connector with internal sealing ring and knockout gasket.

- Extra Long threads to create a raintight seal when connecting EMT to thickwall boxes or enclosures
- Listed UL File E24001

### ZINC DIECAST

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-RT2XL | 1/2” | 50 | 500 |
| 251-RT2XL | 3/4” | 25 | 250 |
| 252-RT2XL | 1” | 15 | 150 |



258-SRT

## RAINTIGHT COMPRESSION CONNECTORS

Compression type connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure.

- NEMA TYPE 2, 3, 3R & 4.
- NPSM Threads. BUNA-N Gasket.
- cULus File No. E24001

### ZINC PLATED STEEL

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-SRT | 1/2” | 25 | 250 |
| 251-SRT | 3/4” | 25 | 250 |
| 252-SRT | 1” | 10 | 100 |
| 253-SRT | 1 1/4” | - | 25 |
| 254-SRT | 1 1/2” | - | 25 |
| 255-SRT | 2” | - | 10 |
| 256-SRT | 2 1/2” | 2 | 10 |
| 257-SRT | 3” | 2 | 10 |
| 258-SRT | 3 1/2” | - | 6 |
| 259-SRT | 4” | - | 6 |



### ZINC PLATED STEEL / INSULATED THROAT - 105°C

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-SRTI | 1/2” | 25 | 250 |
| 251-SRTI | 3/4” | 25 | 250 |
| 252-SRTI | 1” | 10 | 100 |
| 253-SRTI | 1 1/4” | - | 25 |
| 254-SRTI | 1 1/2” | - | 25 |
| 255-SRTI | 2” | - | 10 |
| 256-SRTI | 2 1/2” | 2 | 10 |
| 257-SRTI | 3” | 2 | 10 |
| 258-SRTI | 3 1/2” | - | 6 |
| 259-SRTI | 4” | - | 6 |



253-RT2

## MADE IN THE USA RAINTIGHT COMPRESSION CONNECTORS

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure.

- NEMA TYPE 2, 3, 3R & 4.
- NPT Threads
  - 1/2" and 3/4" have a polyethylene gasket
  - Other sizes have rubber gaskets with steel retaining rings
- 1/2" through 1 1/2" also listed for use with Aluminum EMT
- cULus File No. E24001

### ZINC DIE CAST

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-RT2US | 1/2" | 50 | 500 |
| 251-RT2US | 3/4" | 25 | 250 |
| 252-RT2 | 1" | 15 | 150 |
| 253-RT2 | 1 1/4" | 10 | 100 |
| 254-RT2 | 1 1/2" | 10 | 40 |
| 255-RT2 | 2" | - | 10 |

### ZINC DIE CAST / INSULATED THROAT - 90°C

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-RTI2US | 1/2" | 50 | 500 |
| 251-RTI2US | 3/4" | 25 | 250 |
| 252-RTI2 | 1" | 15 | 150 |
| 253-RTI2 | 1 1/4" | 10 | 100 |
| 254-RTI2 | 1 1/2" | 10 | 40 |
| 255-RTI2 | 2" | - | 10 |
| 256-RTI2 | 2 1/2" | - | 12 |
| 257-RTI2 | 3" | - | 12 |
| 258-RTI2 | 3 1/2" | - | 6 |
| 259-RTI2 | 4" | - | 6 |



250-RT2

## RAINTIGHT COMPRESSION CONNECTORS

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure.

- NEMA TYPE 2, 3, 3R & 4.
- NPT Threads
  - 1/2" and 3/4" have a polyethylene gasket
  - Also listed for use with Aluminum EMT
- cULus File No. E24001

### ZINC DIECAST

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-RT2 | 1/2" | 50 | 500 |
| 251-RT2 | 3/4" | 25 | 250 |

### ZINC DIE CAST / INSULATED THROAT - 90°C

| PART # | TRADE SIZE | UNIT QTY | STD PKG QTY |
|---|---|---|---|
| 250-RTI2 | 1/2" | 50 | 500 |
| 251-RTI2 | 3/4" | 25 | 250 |

## STRONG CONNECTIONS. RAINTIGHT PROTECTION.

- Ideal for Solar boxes and inverters
- Great for Wet/Exposed locations
- Corrosion-resistant die-cast zinc construction
- The 2XL versions accommodate both a locknut and a grounding bushing when used on thick-walled enclosures

QUALITY & INNOVATION

CABLE AND CONDUIT FITTING SOLUTIONS

OVER 100 YEARS

BRIDGEPORT

**To order, contact your local sales representative.**

nsiindustries.com/bridgeport

**800.321.5847**

Scan for Bridgeport's Full Line of Cable & Conduit Fittings

©2025 NSI Industries

BPT_Raintight Comp_EMT_ProdBro
09/2025

NSI INDUSTRIES
800-899-3876
NSIINDUSTRIES.COM