



MRO STAINLESS STEEL

#620-1460

A special formulation containing 316L stainless steel pigment to provide maximum corrosion resistance and protection against weather, sunlight, oil, and water. Dries to a satin finish. Recommended as a topcoat, not a primer. Use of a primer is always beneficial to enhance adhesion and overall durability. Dries quickly and is non-yellowing.

Suggested Uses:

Protect metal
 Touch up appliances
 Paint metal structures
 Touch up welds

Packaging:

UPC Code	043281006897
Cans per case	6
Shipping weight per case	7 lbs.
Container	20 fluid ounce can
Label weight	16 ounces (454 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.79
Solids Content	17%
MIR value	1.16, cannot exceed 1.25
HAPs content	33%
Storage Temperature	40-100F
Application Temperature	50-90F
Abrasion Resistance	Good
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Acrylic lacquer
Shelf life	Guaranteed for 2 years
Food contact rating	Category 21: Acceptable

Dry Time*:

To touch	5 minutes
To topcoat	10 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Low Luster, 15-25*

*as measured on a 60 degree gloss meter

12-1-2021