Slime 2-in-1+

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 9/4/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form	:	Mixture
Trade name	:	Slime 2-in-1+
Product code	:	60198, 60199
Vaporizer	:	Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Intended for general public

Recommended use	:	Tire sealant
Restrictions on use	:	No additional information available

1.4. Supplier's details

Supplier
ITW Global Tire Repair
125 Venture Drive, Suite 210,
San Luis Obispo, CA 93401, USA
Tel: (888) 457-5463 (Toll Free)

1.5. Emergency phone number

Emergency number	:	Chemtel: +1(813)248-0585 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Aerosol, Category 3	H229	Pressurized container; may burst if heated.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US)	:	Warning
Hazard statements (GHS US)	:	H229 - Pressurized container; may burst if heated H317 - May cause an allergic skin reaction
Precautionary statements (GHS US)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read label before use. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapors.

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves.
P302+P352 - If on skin: Wash with plenty of soap and water.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)
Glycerol	CAS-No.: 56-81-5	10 - 30	Not classified
Cellulose	CAS-No.: 9004-34-6	0.1 - 1	Not classified
Silicon dioxide	CAS-No.: 112926-00-8	0.1 - 1	Not classified
Propan-2-ol	CAS-No.: 67-63-0	< 0.1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4	< 0.1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Take off contaminated clothing. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth out with water. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.

Symptoms/effects after eye contact : Redness. Lacrimation. Itching. Blurred vision.

Symptoms/effects after ingestion : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Alcohol-resistant foam. Carbon dioxide. Water spray. Use extinguishing agent suitable for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : In case of fire and/or explosion do not breathe fumes. Burning produces stinking and toxic fumes.

Explosion hazard : Contains gas under pressure; may explode if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all contact with skin, eyes, or clothing.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures	:	Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing spray. Do not get in eyes, on skin, or on clothing. Do not touch or walk on the spilled product. No action shall be taken without appropriate training or involving any personal risk.

For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel.
Environmental precautions	:	Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment	:	Stop leak, if possible without risk. Do not touch or walk on the spilled product. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	:	Move containers from spill area. Leave the product to evaporate. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean area with detergent and water after spill clean-up. Prevent entry to sewers and public waters. Keep in suitable, closed containers for disposal.
Other information	:	Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

For further information refer to section 13,For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Avoid breathing spray. Wear personal protective equipment. Avoid contact with skin and eyes. Empty containers retain product residue and can be hazardous. Pressurized container: Do not pierce or burn, even after use. Avoid release to the environment.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	:	Store in a well-ventilated place. Keep cool. Store away from other materials. Refer to Section 10 on Incompatible Materials. Keep away from food, drink and animal feed. Do not store in unlabelled containers. Store in accordance with local, regional, national or international regulation.
Incompatible products	:	Oxidising agents.
Incompatible materials	:	Direct sunlight. Heat sources.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Cellulose (9004-34-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Cellulose
ACGIH® TLV® TWA	10 mg/m³

Cellulose (9004-34-6)	
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Cellulose
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Cellulose (paper fiber)
Cal/OSHA PEL (OEL TWA)	10 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Cellulose
NIOSH REL 10h TWA	10 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Glycerol (56-81-5)	
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Glycerin mist
Cal/OSHA PEL (OEL TWA)	10 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)

Silicon dioxide (112926-00-8)	
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, amorphous, precipitated and gel
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formula: (80 mg/m3 / (%SiO2)) for mg/m3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - NIOSH - Occupational Exposure Limits	
Local name	Silica, amorphous, precipitated and gel
NIOSH REL 10h TWA	6 mg/m³

Silicon dioxide (112926-00-8)	
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-3 Mineral Dusts (NIOSH Pocket Guide to Chemical Hazards (NPG))
Propan-2-ol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH® TLV® TWA	491 mg/m³
	200 ppm
ACGIH® TLV® STEL	984 mg/m³
	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL TWA	980 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
Cal/OSHA PEL (OEL TWA)	980 mg/m³
	400 ppm
Cal/OSHA STEL	1225 mg/m³
	500 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Isopropyl alcohol
NIOSH REL 10h TWA	400 ppm
NIOSH REL (STEL)	500 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Ensure exposure is below occupational exposure limits (where available). Avoid all unnecessary exposure.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:
Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Eye protection:
Use splash goggles when eye contact due to splashing is possible

Skin and body protection:
Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. All respirators must conform to specifications for efficiency and performance indicated by OSHA Standard 29 CFR 1910.134 and NIOSH Standards

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Gas
Appearance	:	Aerosol.
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Flammability (solid, gas)	:	No data available
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Explosion limits	:	No data available
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Contains gas under pressure; may explode if heated.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization: Will not occur.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-methylisothiazol-3(2H)-one (2682-20-4)	
ATE US (oral)	100 mg/kg
ATE US (dermal)	300 mg/kg
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.5 mg/l/4h
ATE US (dust, mist)	0.05 mg/l/4h

Glycerol (56-81-5)	
LD50 oral rat	12600 mg/kg
LD50 dermal rabbit	> 18700 mg/kg

Silicon dioxide (112926-00-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Propan-2-ol (67-63-0)	
LD50 oral rat	4570 mg/kg
LD50 dermal rabbit	13400 mg/kg
LC50 Inhalation - Rat	30 mg/l/4h
LC50 Inhalation - Rat [ppm]	16000 ppm (8 h)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Propan-2-ol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not applicable

Slime 2-in-1+	
Vaporizer	Aerosol

Symptoms/effects after inhalation : Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact : May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact : Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion : Not expected to present a significant hazard under anticipated conditions of normal use.
Other information : No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

2-methylisothiazol-3(2H)-one (2682-20-4)	
LC50 - Fish [1]	6 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	1.68 mg/l (48 h, Daphnia sp., OECD 202)
EC50 - Other aquatic organisms [1]	34.6 mg/l (3 h, DIN 38412-3)
EC50 72h - Algae [1]	0.157 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)
NOEC chronic fish	2.1 mg/l (28 d, Pimephales promelas, OECD 210)
NOEC chronic crustacea	0.55 mg/l (21 d, Daphnia sp., OECD 211)
NOEC chronic algae	0.03 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)

Glycerol (56-81-5)	
LC50 - Fish [1]	> 10000 mg/l (Leuciscus idus)
EC50 - Crustacea [1]	> 10000 mg/l (Daphnia magna)
EC50 - Other aquatic organisms [1]	> 10000 mg/l (16 h, Pseudomonas putida)

Silicon dioxide (112926-00-8)	
NOEC chronic fish	> 10000 ppm (96 h, Brachydanio rerio)

Silicon dioxide (112926-00-8)	
NOEC chronic crustacea	> 1000 ppm (24 h, Daphnia magna)

Propan-2-ol (67-63-0)	
LC50 - Fish [1]	9640 mg/l (96 h, Pimephales promelas, flow-through)
EC50 - Crustacea [1]	13299 mg/l (48 h, Daphnia magna)

12.2. Persistence and degradability

Slime 2-in-1+	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Slime 2-in-1+	
Bioaccumulative potential	No data available concerning bioaccumulation.

2-methylisothiazol-3(2H)-one (2682-20-4)	
BCF - Fish [1]	3.16
Partition coefficient n-octanol/water (Log Kow)	-0.32 (OECD 117)

Silicon dioxide (112926-00-8)	
BCF - Fish [1]	0

Propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (25 °C)

12.4. Mobility in soil

Slime 2-in-1+	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No other effects known.
Effect on global warming : No known effects from this product.
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1950	UN1950	1950	1950

DOT	TDG	IMDG	IATA
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, non-flammable
14.3. Transport hazard class(es)			
2.2	2.2	2.2	2.2
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1950

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

Emergency Response Guide (ERG) Number : 126

IMDG

Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

Special provision (IATA)	:	A98, A145, A167, A802
PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
ERG code (IATA)	:	2L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
Silicon dioxide	CAS-No. 112926-00-8	0.1 - 1%
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S		
2-methylisothiazol-3(2H)-one	CAS-No. 2682-20-4	< 0.1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Propan-2-ol	CAS-No. 67-63-0	< 0.1%

15.2. International regulations

CANADA

2-methylisothiazol-3(2H)-one (2682-20-4)
Listed on the Canadian DSL (Domestic Substances List)

Cellulose (9004-34-6)
Listed on the Canadian DSL (Domestic Substances List)

Glycerol (56-81-5)
Listed on the Canadian DSL (Domestic Substances List)

Silicon dioxide (112926-00-8)
Listed on the Canadian DSL (Domestic Substances List)

Propan-2-ol (67-63-0)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

2-methylisothiazol-3(2H)-one (2682-20-4)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Cellulose (9004-34-6)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Glycerol (56-81-5)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Silicon dioxide (112926-00-8)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Propan-2-ol (67-63-0)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 9/4/2025
Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled

Full text of hazard classes and H-statements	
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Abbreviations and acronyms	
ACGIH	American Conference of Government Industrial Hygienists
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS-No.	Chemical Abstract Service number
DOT	Department of Transport
DSL	Canada DSL (Domestic Substances List)
EC50	Median effective concentration
EC-No.	European Community number
EPA	Environmental Protection Agency
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NDSL	Canada NDSL (Non-Domestic Substances List)
NIOSH	National Institute for Occupational Safety and Health
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PPE	Personal protection equipment
SDS	Safety Data Sheet
TLV	Threshold Limit Value
TWA	Time Weighted Average

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.