




FEATURES

With their smooth, flat and edgeless design, Oscar family recessed luminaires become a seamless part of ceiling decor. With 3 different light modules suited for ambient and accent lighting, the Oscar family is as highly functional as it is visually appealing. Numerous ordering options allow for further functional and artistic customization. Oscar recessed luminaires are available in larger sizes with higher lumen packages making them ideal for both residential and commercial settings.



SPECIFICATIONS

FIXTURE BODY	18 gauge powder coated steel body. Aluminum powder coated trim or trimless mesh plate
INSTALLATION TYPE	Remodel/existing ceiling N/C plate, IC Box on page 2
CUT HOLE	Trim: 4" x 4" Trimless: 4" x 4" Trimless Wood Ceiling Please contact us for detail
COLOR FINISH	Black/White/Custom
LIGHT MODULE	High output, high efficiency LED COB. Lumen Maintenance: 70% @ 50,000 hrs
INPUT VOLTAGE	120V - 277V
WATTAGE	(10W) IC Rated (15W) Non-IC Rated (26W) Non-IC Rated
POWER SUPPLY	ERP 10W, Constant Current 250mA power supply ERP 15W, Constant Current 350mA power supply ERP 26W, Constant Current 700mA power supply Minimum operating temperature: -30° Enclosed in a Junction box with 12" flexible cable to mate to module connector
BEAM ANGLE	Wall wash
CRI	90+
DIMMING	TRIAC/ELV/0-10V
DELIVERED LUMENS	10W IC: 420 LM, 10H IC: 565LM, 15W Non-IC: 780 LM, 26W Non-IC: 1200 LM
CCT OPTIONS	2700K/3000K/3500K/4000K
REFLECTORS	(W) Wide
DIFFUSERS	Built on clear protective lens
APPROVAL	Damp
ELECTRICAL APPROVAL	
WARRANTY	

SPECIFICATION GUIDE

OSCAR	4	SHAPE		TRIM/ TRIMLESS		FINISHES		LIGHT MODULE		BAFFLE FINISHES		WATTAGE		CCT	BEAM ANGLE	DIFFUSER		ADD-ONS	
OSC	4	S	SQUARE	T	TRIM	01	BLACK	WL	WALL WASH	01	MATTE BLACK	10	10W	27	W	CL	CLEAR	EM	EMERGENCY MICRO INVERTER*
				TL	TRIMLESS	02	WHITE			02	MATTE WHITE	10 H	High Lumen 10W	30					
				WC	TRIMLESS WOOD CEILING							15	15W	35					
												26	26W	40					
						* Part# 47184-015 Sold Seperate, see page 2 for details.													

ORDERING GUIDE EXAMPLE:

Oscar / 4 / Square / Trim / White / Wall Wash / White / 15W / 2700K / 95° Beam Angle / Clear Diffuser

CODE: OSC-4-S-T-02-WL-02-15-27-W-CL

* Part# 47184-015 Sold Separate, see page 2 for details.

REFLECTOR OPTIONS



Wall wash

DIFFUSER OPTIONS




Clear Lens (CL)

NEW CONSTRUCTION PLATES + IC BOXES




NEW CONSTRUCTION PLATE TRIM/TRIMLESS
44838-010

CUT HOLE:
Trim & Trimless: 4" x 4"




TRIM AT/IC Box: 46749-017



CUT HOLE:
Trim & Trimless: 4" x 4"





DRIVERS

- Compatible with TRIAC (forward-phase or leading-edge) ELV (reverse-phase or trailing edge) and 0-10V dimmers.
- ESSxxxW models: TRIAC and ELV dimming only at 120 Vac
- ESSxxxW models: ELV dimming only at 230 Vac
- 90° C maximum case hot spot temperature
- Class 2 power supply
- Lifetime: 50,000 hours at 70° case hot spot temperature (some models have a higher lifetime)
- IP64-rated (IP66 for ESST) case with silicone-based potting
- Protections: Output open load, over-current and short-circuit (hiccup), and over-temperature with auto recovery.
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class B (120 Vac) and Class A (277 Vac), and EN55015 (CISPR 15) at 220, 230, and 240 Vac.
- Complies with ENERGY STAR®, DLC (DesignLight Consortium®) and CA Title 24 technical requirements
- Worldwide safety approvals







26W 1-LIGHT Square WALL WASH NARROW CLEAR





26W 1-LIGHT Square WALL WASH MEDIUM CLEAR





26W 1-LIGHT Square WALL WASH WIDE CLEAR

3" Oscar



Medium Aperture Square - Wall Wash
PHOTOMETRICS (Imperial)



26W 1-LIGHT Square WALL WASH NARROW CLEAR



26W 1-LIGHT Square WALL WASH MEDIUM CLEAR



26W 1-LIGHT Square WALL WASH WIDE CLEAR