


Mini White



**New
and
Improved**

**FP3578/MG
Condensate
Removal Pump**

The ultra quick fit Mini White is designed to be installed beneath high wall indoor units and offers easy access for future maintenance.

Key Features:

- Univolt
- Compact and discreet
- Clear, removable reservoir
- As low as 21 dB(A)
- 2-year warranty

Range Suitability:

- 26kW / 90,000BTU/h / 7.5 tons
- Ductless mini split systems
- Perfect for- residential and light commercial applications where easy maintenance and reliable performance is key

In the Box:

- Mini White 4.5 Gen Pump
- Hardwired 5' (1.5m) Power Cable
- Fitting template (on the box)
- Quick Start Guide

Product Specifications:

Max. flow	5 US Gallons (20L/h) @ 0m head
Max. rec. head	33ft./10m
Min. dB(A) @ 1m	21dB(A)*
Power supply	100-250V, 50/60Hz, 0.16A/5W
Rated	Continuous
Class	II
Max. unit output	26kW / 90,000BTU/h / 7.5 tons
Max. water temp	104°F (40°C)
IP Protection	IP24
Inlet o/d	5/8"-7/8" (Ø16mm-Ø23mm)
Outlet o/d	1/4" (Ø6mm)
Safety switch	High level safety wires N.C. contacts, 250 VAC, 3A max
Self priming	✓

Ensure ALL cleaning chemicals are flushed out of the reservoir after use.

*Assuming solid wall construction with a 2kW unit.



Mini White | 100-250VAC, 50Hz/60Hz US Gallons

