



PART NUMBER	NUMBER OF PORTS	WIRE RANGE CLASS B,C,D	WIRE RANGE CLASS K,M,I	LENGTH
IPLG6-3	3	6 - 14 AWG	6 - 14 AWG	1.55
IPLG6-4	4	6 - 14 AWG	6 - 14 AWG	1.97
IPLG6-6	6	6 - 14 AWG	6 - 14 AWG	2.81

CONTACT NSi FOR SALES @ 800.321.5847

		POLARIS SALES . CO . INC	
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED #6 CONNECTOR GREY FINE STRANDED	
<small>NAME</small>		<small>DATE</small>	
<small>DRAWN BY</small> S.PARRY		<small>DATE</small> 4/5/2022	
<small>MATERIAL:</small> 6061-T6511 ALUMINUM		<small>SCALE:</small> 1:1	
<small>DWG. NO.</small>		<small>SHEET:</small> 1 OF 1	
IPLG6-_SERIES			

- NOTES:
1. CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
 2. UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
 3. RATED FOR 90°C COPPER CONDUCTOR.
 4. COLD TEMPERATURE RATED TO -45°C.
 5. HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.