

MRO RUST PREVENTATIVE PRIMER

#1-1407 Red Oxide, #1-1431 Light Gray



This is an industrial grade primer specifically formulated for resistance to rust and corrosion. Provides excellent adhesion to steel, hides easily, and can be applied by brush or spray. Topcoat with MRO enamels for maximum protection.

Suggested Uses:

Railings
 Storage tanks
 Structural steel
 Piping
 Steel doors

Packaging:

UPC Code (red oxide):	043281004718
UPC Code (light gray):	043281004817
Cans per case	4
Container	1 gallon can (3.8 LITERS)
Shipping Classification	UN 1263
Hazard Class	3
Flammability	WARNING! Combustible liquid and vapor.

Properties:

Coverage	Up to 300 square feet
Cleanup	Paint/lacquer thinner
Flash point	104F
Solids Content	74%, depends on color
VOC content	~167 g/L, depends on color
HAPS Content	0
Viscosity	90-99 Kreb Units
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Alkyd
Density	10.7 pounds per gallon
Shelf life	1 year
Food contact rating	No

Dry Time*:

To touch	30 minutes
To recoat	3 hours

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick
 coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss
 meter

12-2-2021