

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Slime Tubeless Sealant

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Intended for general public  
Use of the substance/mixture : Tire sealant  
Restrictions on use : No additional information available

#### 1.4. Supplier's details

**Supplier**  
ITW Global Tire Repair, Inc.  
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401, USA  
Tel: (888) 457-5463 (Toll Free)

#### 1.5. Emergency phone number

Emergency number : Chemtel: +1(813)248-0585 (International)

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Full text of H statements : see section 16		

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
Precautionary statements (GHS US) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.  
P261 - Avoid breathing vapours.  
P264 - Wash hands thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves, protective clothing, eye and face protection.  
P302+P352 - If on skin: Wash with plenty of soap and water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P337+P313 - If eye irritation persists: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

Name	Product identifier	%	GHS US classification
Natural rubber latex	CAS-No.: 9006-04-6	7 - 13	Skin Sens. 1B, H317
Glycerol	CAS-No.: 56-81-5	5 - 10	Not classified
Alcohols, C12-14-secondary, ethoxylated	CAS-No.: 84133-50-6	1 - 5	Skin Irrit. 2, H315 Eye Dam. 1, H318
Cellulose	CAS-No.: 9004-34-6	0.1 - 1	Not classified
Silicon dioxide	CAS-No.: 112926-00-8	0.1 - 1	Not classified
Ammonia	CAS-No.: 1336-21-6	0.1 - 1	Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	CAS-No.: 4719-04-4	0.1 - 1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Quartz (SiO <sub>2</sub> )	CAS-No.: 14808-60-7	< 0.1	Carc. 1A, H350 STOT RE 1, H372
Magnesium oxide	CAS-No.: 1309-48-4	< 0.1	Not classified

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Get medical advice/attention.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Abdominal pain.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry powder. Alcohol-resistant foam. Carbon dioxide. Water spray. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: In case of fire and/or explosion do not breathe fumes. Burning produces stinking and toxic fumes. Heating will cause a rise in pressure with a risk of bursting.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all contact with skin, eyes, or clothing.
------------------	---

#### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Do not touch or walk on the spilled product. No action shall be taken without appropriate training or involving any personal risk.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Do not touch or walk on the spilled product. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Caution : this product can cause the floor to be slippery. Move containers from spill area. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean contaminated surfaces with an excess of water. Prevent entry to sewers and public waters.

Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

For further information refer to section 13, For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapor concentrations. Provide local exhaust or general room ventilation. Avoid breathing vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid release to the environment. Empty containers retain product residue and can be hazardous.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in a dry place. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep only in original container. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep away from food, drink and animal feed. Store in accordance with local, regional, national or international regulation.

Incompatible materials : Direct sunlight. Heat sources.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

Glycerol (56-81-5)	
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL TWA	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Glycerin mist
Cal/OSHA PEL (OEL TWA)	10 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Glycerol (56-81-5)</b>	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
<b>Cellulose (9004-34-6)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Cellulose
ACGIH OEL TWA	10 mg/m <sup>3</sup>
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2023
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Cellulose
OSHA PEL TWA	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - Cal/OSHA - Occupational Exposure Limits</b>	
Local name	Cellulose (paper fiber)
Cal/OSHA PEL (OEL TWA)	10 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
Local name	Cellulose
NIOSH REL 10h TWA	10 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
<b>Quartz (SiO<sub>2</sub>) (14808-60-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Quartz (Total Dust) (Silica: Crystalline)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m <sup>3</sup> / (%SiO <sub>2</sub> +2)) for mg/m <sup>3</sup> . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
<b>USA - Cal/OSHA - Occupational Exposure Limits</b>	
Local name	Quartz
Cal/OSHA PEL (OEL TWA)	0.05 mg/m <sup>3</sup> (Silica, crystalline, respirable dust)

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (SiO <sub>2</sub> ) (14808-60-7)	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Quartz (Silica, crystalline, respirable dust)
NIOSH REL 10h TWA	0.05 mg/m <sup>3</sup>
Remark (NIOSH)	Ca = Potential occupational carcinogens
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Magnesium oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Magnesium oxide
ACGIH OEL TWA	10 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT; metal fume fever. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Magnesium oxide fume - Total Particulate
OSHA PEL TWA	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Magnesium oxide fume, as Mg
Cal/OSHA PEL (OEL TWA)	10 mg/m <sup>3</sup>
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
Natural rubber latex (9006-04-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Natural rubber latex, as inhalable allergenic proteins
ACGIH OEL TWA	0.0001 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Resp sens. Notations: Skin; DSEN; RSEN
Regulatory reference	ACGIH 2024
Silicon dioxide (112926-00-8)	
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, amorphous, precipitated and gel
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formula: (80 mg/m <sup>3</sup> / (%SiO <sub>2</sub> )) for mg/m <sup>3</sup> . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - NIOSH - Occupational Exposure Limits	
Local name	Silica, amorphous, precipitated and gel
NIOSH REL 10h TWA	6 mg/m <sup>3</sup>

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Silicon dioxide (112926-00-8)	
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-3 Mineral Dusts (NIOSH Pocket Guide to Chemical Hazards (NPG))
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Avoid all unnecessary exposure. Ensure exposure is below occupational exposure limits (where available).
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment. All respirators must conform to specifications for efficiency and performance indicated by OSHA Standard 29 CFR 1910.134.

Hand protection:
Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer
Eye protection:
Chemical goggles or safety glasses
Skin and body protection:
Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: According to product specification
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization: Will not occur.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Glycerol (56-81-5)	
LD50 oral rat	12600 mg/kg
Quartz (SiO2) (14808-60-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)	
ATE US (oral)	500 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens



# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

Quartz (SiO <sub>2</sub> ) (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

Slime Tubeless Sealant	
Viscosity, kinematic	No data available
Symptoms/effects after inhalation	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Abdominal pain.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Glycerol (56-81-5)	
LC50 - Fish [1]	51000 – 57000 mg/l (96 h, Oncorhynchus mykiss)
Silicon dioxide (112926-00-8)	
NOEC chronic fish	> 10000 ppm (96 h)
NOEC chronic crustacea	> 1000 ppm (24 h, Daphnia magna)

### 12.2. Persistence and degradability

Slime Tubeless Sealant	
Persistence and degradability	Biodegradability in water: no data available.

### 12.3. Bioaccumulative potential

Slime Tubeless Sealant	
Bioaccumulative potential	No data available concerning bioaccumulation.
Glycerol (56-81-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.76

### 12.4. Mobility in soil

Slime Tubeless Sealant	
Ecology - soil	No additional information available.

### 12.5. Other adverse effects

Ozone : Not classified

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other adverse effects : No other effects known.  
Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal must be carried out using appropriate EWC code.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not dispose of the packaging without first carrying out the necessary cleaning.  
Ecological waste information : Avoid release to the environment.

### SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

Not regulated for transport

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated  
Proper Shipping Name (TDG) : Not regulated  
Proper Shipping Name (IMDG) : Not regulated  
Proper Shipping Name (IATA) : Not regulated

#### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not regulated

**TDG**  
Transport hazard class(es) (TDG) : Not regulated

**IMDG**  
Transport hazard class(es) (IMDG) : Not regulated

**IATA**  
Transport hazard class(es) (IATA) : Not regulated

#### 14.4. Packing group

Packing group (DOT) : Not regulated  
Packing group (TDG) : Not regulated  
Packing group (IMDG) : Not regulated  
Packing group (IATA) : Not regulated

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Transport in bulk

Not applicable

#### 14.7. Special precautions for user

**DOT**  
Not regulated

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### TDG

Not regulated

### IMDG

Not regulated

### IATA

Not regulated

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
Natural rubber latex	CAS-No. 9006-04-6	7 - 13%
Silicon dioxide	CAS-No. 112926-00-8	0.1 - 1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Ammonia	CAS-No. 1336-21-6	0.1 - 1%

Ammonia (1336-21-6)	
CERCLA RQ	1000 lb

### 15.2. International regulations

#### CANADA

Glycerol (56-81-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Cellulose (9004-34-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Alcohols, C12-14-secondary, ethoxylated (84133-50-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Quartz (SiO <sub>2</sub> ) (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Magnesium oxide (1309-48-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Natural rubber latex (9006-04-6)	
Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)	

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Ammonia (1336-21-6)

Listed on the Canadian DSL (Domestic Substances List)

### Silicon dioxide (112926-00-8)

Listed on the Canadian DSL (Domestic Substances List)

### 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)

Listed on the Canadian DSL (Domestic Substances List)

## EU-Regulations

No additional information available

## National regulations

### Glycerol (56-81-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Cellulose (9004-34-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Alcohols, C12-14-secondary, ethoxylated (84133-50-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Quartz (SiO<sub>2</sub>) (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Magnesium oxide (1309-48-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Ammonia (1336-21-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Silicon dioxide (112926-00-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date : 1/2/2025  
Data sources : Supplier's safety documents. ECHA (European Chemicals Agency).  
Training advice : Training staff on good practice.

#### Full text of hazard classes and H-statements

H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

#### Abbreviations and acronyms

ACGIH	American Conference of Government Industrial Hygienists
AIHA	American International Health Alliance
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS-No.	Chemical Abstract Service number
DOT	Department of Transport
DSL	Canada DSL
EC50	Median effective concentration
EC-No.	European Community number
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NDSL	Canada NDSL
NIOSH	National Institute for Occupational Safety and Health

# Slime Tubeless Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PPE	Personal protection equipment
SDS	Safety Data Sheet

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.