## 1 Identification of the substance and manufacturer

Tra	de	na	me	

## Product code: Recommended use: Uses advised against: Manufacturer/Supplier:

## **GRAY PRIMER (MRO) GALLONS**

0000011431 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com

Emergency telephone number:

## 2 Hazard(s) identification

z nazaru(s) identification	
Classification of the substance	or mixture
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Acute Toxicity - Oral 4	H302 Harmful if swallowed.
Skin Irritation 2	H315 Causes skin irritation.
Carcinogenicity 2	H351 Suspected of causing cancer. Route of exposure: Inhalation.
Specific Target Organ Toxicity - S	
Specific Target Organ Toxicity - R Additional information:	epeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.
GHS Hazard pictograms	
	GHS02 GHS07 GHS08
Signal word Hazard statements	Danger Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Suspected of causing cancer. Route of exposure: Inhalation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients		
Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.		
Dangerous components:		
1317-65-3 Calcium Carbonate		25-50%
98-56-6 p-Chlorobenzotrifluoride		10-15%
64742-47-8 Mineral Spirits		5-10%
13463-67-7 titanium dioxide		5-10%
557-05-1 zinc stearate		1-5%
4 First-aid measures   After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.   After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.   After swallowing: Rinse mouth with water. Do not induce vomiting.   Most important symptoms and effects: No further relevant information available.   Indication of any immediate medical attention needed: No further relevant information available.		
5 Fire-fighting measures	No further relevant information available	

Special hazards:

No further relevant information available.

(Contd. on page 2)

Page 2/3

Revised On 01/03/2024

Protective equipment for firefighters:	(Contd. of page No special measures required.
Accidental release measures	
	Not required.
Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Handling and storage	
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditior Store locked up.
Exposure controls/personal prote	ection
Components with limit values that re	equire monitoring at the workplace:
557-05-1 zinc stearate PEL (USA) Long-term value: 15* 5** m	ng/m³
` total dust **respirable frac	stion
REL (USA) Long-term value: 10* 5** m *total dust **respirable fract	
TLV (USA) Long-term value: 10* 3** m *inhalable, **respirable part	
Hygienic protection:	Immediately remove all soiled and contaminated clothing. Wash hands after use.
Breathing equipment: Hand protection:	Do not eat or drink while working. Not required. Nitrile gloves.
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles
Physical and chemical properties	
Appearance: Odor threshold:	Liquid. Not determined.
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. 139 °C (282.2 °F)
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Highly flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. Not determined. Not determined.
Vapor pressure: Vapor density Evaporation rate Partition coefficient: n-octonal/water	Not determined. Not determined. Not determined. r: Not determined.
Solubility: Viscosity: Water:	Not determined. Not determined. 0.0 %
Stability and reactivity	
Conditions to avoid: Possibility of hazardous reactions:	No decomposition if used according to specifications. No dangerous reactions known. No further relevant information available.
	No dangerous decomposition products known.

Printing date 01/03/2024

Trade name: GRAY PRIMER (MRO) GALLONS

Revised On 01/03/2024

Page 3/3

	(0	- 4	 2

	(Contd. of page 2)		
11 Toxicological information			
LD/LC50 values that are relevant for	or classification:		
13463-67-7 titanium dioxide			
Dermal LD50 >10,000 mg/kg			
Inhalative LC50/4 h >6.82 mg/l (rat)			
Information on toxicological effect			
Skin effects: Eve effects:	No irritant effect. No irritating effect.		
Sensitization:	No sensitizing effects known.		
	5		
12 Ecological information			
Aquatic toxicity:	Hazardous for water, do not empty into drains.		
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.		
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated		
	solvents.		
Bioaccumulative potential:	No further relevant information available.		
Mobility in soil: Other adverse effects:	No further relevant information available.		
	No further relevant information available.		
12 Disposal considerations			
13 Disposal considerations	state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be		
disposed of responsibly. Do not heat	or cut empty containers with electric or gas torches.		
Recommendation:	Completely empty cans should be recycled.		
Recommended cleansing agent:	Water, if necessary with cleansing agents.		
14 Transport information			
UN-Number			
ADR Transport hazard class(es):	1263 Paint		
Class	3 Flammable liquids		
Marine pollutant:	No		
Special precautions for user: EMS Number:	Warning: Flammable liquids F-E,S-E		
UN "Model Regulation":	UN1263, Paint, 3, II		
15 Regulatory information			
SARA Section 355 (extremely haza	rdous substances):		
None of the ingredients in this produc			
SARA Section 313 (Specific toxic of			
557-05-1 zinc stearate			
7779-90-0 zinc phosphate			
Toxic Substances Control Act			
(TSCA):	All hazardous ingredients are found on the inventory list of substances.		
Canadian Domestic Substances Li (DSL):	All ingredients are listed or exempted.		
Consumer Product Safety			
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
California Proposition 65 chemical			
98-56-6 p-Chlorobenzotrifluoride			
13463-67-7 titanium dioxide			
100-41-4 ethyl benzene 1333-86-4 Carbon black			
Prop 65 chemicals known to cause birth defects or reproductive harm:			
None of the ingredients is listed.	e pirtil delects or reproductive narm:		
EPA:			
557-05-1 zinc stearate 7779-90-0 zinc phosphate			
	D, I, II		
16 Other information			
Contact:	Regulatory Affairs		