


NSI INDUSTRIES LLC
EASY-TWIST™ GUSSET BAGS
WWC-R-B_ET-TOWC_Packaging_Bag
v4
255mm x 330mm
07/2024

DO NOT PRINT CYAN
LINE-PLACEMENT ONLY



The colors on the package are
CMYK, but they should match the
spot colors shown above.

255mm

(255)2x330mm 底(60)2mm

拉鏈中心35mm

打角20mm

330mm

WWC-R-B

EASY-TWIST™

WINGED WIRE CONNECTORS

SAME GRIP

LESS TWISTS

Red Winged Connectors

Raccords Ailes Rouge

Conectores Rojos Con Clip

De Seguridad

500

Qty/Qte/Ctd

22-6 AWG

Solid & Stranded

60mm

60mm

330mm

NSI Industries

800.321.5847

nsiindustries.com

WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

ADVERTENCIA: Cáncer y este daño reproductivo - www.P65Warnings.ca.gov.

⚠️ ADVERTISSEMENT: Cancer et troubles de l'appareil reproducteur - www.P65Warnings.ca.gov.

For complete listing of wire combinations and voltage ratings, scan QR code or contact Customer Service at 800-321-5847

Please note: WWC-GR is not rated for 1 #10 and 3 #10 | WWC-B is not rated for 4 #12 and 5 #12

	AWG WIRE COMBINATIONS	3 #22	4 #22	2 #18	3 #16	2 #14	1 #10	3 #12	4 #12	3 #10	5 #12	4 #10	2 #6
WWC-Y													
WWC-T													
WWC-R													
WWC-GR													
WWC-G													
WWC-B													

UL LISTED

WIRE CONNECTORS

010072

ROHS COMPLIANT

REACH COMPLIANT

SCAN ME

QR CODE

Made in Taiwan

Fabrique en Taïwan

Hecho en Taiwán

6 52381 356194 5

Barcode

INSTRUCTIONS

Strip solid wires 5/8" (15.9 mm)

Pre-twisting unnecessary, hold stripped wires together with ends even. Lead

Align any frayed strands or conductors

Push wires into connector and screw on until two

twists are visible in wires

SPÉCIFICATIONS

Listed as a pressure-type wire connector

Temperature Rating: 105°C (221°F) max

Voltage Rating: 600V max building wiring

1000V Max. signs or luminaires

FOR USE WITH COPPER TO

COPPER CONDUCTOR

INSTRUCCIONES

Desdoble los cables sólidos de 5/8" (15.9 mm)

No es necesario que estén previamente trenzados, sostenga los cables destrorados juntos con las puntas al mismo nivel. Meta un poco los cables trenzados o conductores

Alinee los cables trenzados o conductores

Conduzca los cables ligeramente los cables trenzados

Conduzca los cables trenzados o conductores

Alinee los brins ou les conducteurs

Alignez les brins ou les conducteurs

effilochés

Poussez les fils dans le connecteur et vissez jusqu'à ce que deux torsions soient visibles jusqu'à

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

Turn off power before installing or removing connectors / Couper l'alimentation avant d'installer ou de retirer les raccords / Apague la alimentación antes de instalar o retirar los conectores

WARNING / PRECAUTION / ADVERTISSEMENT

WWC-R-B

DIELINE IS SPOT COLOR AND 100% CYAN
WINDOW IS SPOT COLOR AND 15% CYAN