



WIRELESS VACUUM GAUGE



VG640TL



POWERED BY SUPCO[®] TECHLINK[™]

www.supco.com



PRODUCTIVITY ELEVATED.

WIRELESS VACUUM GAUGE VG640TL

Technicians can now use the power of their mobile device along with the free **Supco® Techlink™ App** to enhance job-site productivity while working with a precision digital vacuum gauge.

The **Supco® Techlink™ VG640TL** allows for real-time remote Bluetooth® monitoring from up to 200 ft away with a mobile device and reporting of the evacuation process, which can be downloaded to PDF and Excel/CSV formats.

With a revolutionary contaminant resistant *Lifetime Sensor* and an unmatched resolution as low as .5 Micron, the **VG640TL** can be used as a standalone gauge or wirelessly paired with a mobile device for access to a convenient suite of remote features for today's technician.

FEATURES

- Easy to use - configure in seconds with an iOS® or Android® device
- Contaminant & oil resistant *Lifetime Sensor*
- Bluetooth® Low Energy (BTLE) standard (v4.1)
- Display resolution: As low as 0.5 Micron
- Standard 1/4" Male Flare Fitting
- Vacuum Range: 0 - 19000 Micron (0 - 2600 Pascal)
- Units: Micron, milliBar, Pascal, Torr, milliTorr
- Accuracy: +/-7% or +/-10 Micron (1.3 Pascal), whichever is larger (50 to 2000 Micron) at 75°F (24°C)
- Instant warm-up and response time
- Large, back-lit LCD display
- Temperature compensated for accuracy
- Auto power-off function
- Battery life up to 400 hours continuous use
- Includes vacuum gauge coupler, convenient magnetic holding strap & Quick Start guide



SUPCO® TECHLINK™ DIAGNOSTIC APP

- Remote Bluetooth® monitoring from up to 200 ft away
- Real time viewing & logging with graphs
- Low & high vacuum alerts
- Record & export the evacuation process to PDF and Excel / CSV formats
- Time evacuation & vacuum decay process

Learn more and download

SUPCOTECHLINK.COM



supco.com



800 333 9125

A Sealed Unit Parts Co., Inc. Solution

F670