

# LTE101

Indoor/Outdoor Access Point

## LTE101: Dual-Carrier Indoor/Outdoor 4G/LTE Solution for Business Connectivity

The Wilson Connectivity LTE101 delivers powerful 4G/LTE capabilities for indoor and outdoor business environments through its dual-carrier design. This robust indoor/outdoor access point ensures reliable connectivity for a wide range of commercial applications. With its two-carrier configuration, the LTE101 offers the bandwidth and flexibility needed for data-intensive operations in corporate campuses, industrial sites, and outdoor business venues. It's the ideal choice for enterprises looking to maintain strong, consistent wireless connections for their outdoor operations, supporting everything from IoT deployments to mobile workforce solutions. This also provides suitable indoor coverage in harsh environments, where typical indoor access points cannot survive, or where more custom indoor antenna configurations are required.



In DC mode, each carrier is treated as an independent cell, supporting 96+96 users with each cell supporting 5, 10, 15, or 20 MHz bandwidth. Using an LTE101 in DC mode simplifies and streamlines the deployment of split sectors. This product comes with a standard one-year warranty; an extended warranty is available.

### Technology

<b>Standard</b>	LTE TDD RAN (3GPP Release 15 compliant)
<b>TDD UL/DL Configuration</b>	1, 2, 6 (with Special Subframe Configuration 7)
<b>Frequency Band</b>	B48 (3550MHz–3700MHz)
<b>Channel Bandwidth</b>	SC: 5/10/15/20MHz CA: 40MHz as maximum aggregated bandwidth
<b>Multiplexing</b>	MIMO: 2x2 (DL)
<b>Security</b>	Radio: SNOW3G/AES-128 Backhaul: IPsec (X.509 AES-128, AES-256, SHA-128, SHA-256)

## Highlights

Standard LTE TDD Band 48

GUI-based local and remote Web management

Excellent Non-Line-of-Sight (NLOS) coverage

Peak rate: Up to DL 290Mbps and UL 70 Mbps with 2x20MHz bandwidth

2CC DL/UL CA improves the spectrum efficiency of fragmented spectrum resources

Suitable for private and public deployments; any IP-based backhaul can be used, including public transmission protected by Internet Protocol Security (IPsec)

96 RRC connected users per carrier (96+96 in DC mode), upgradeable to higher capacity in future releases

Configured out-of-the-box to work with The Wilson Platform

Supports transparent Bridge Mode

Supports Citizens Broadband Radio Service (CBRS)

Interoperable with standard LTE Evolved Packet Core (EPC)

Supports TR-069 network management interface

Lower power consumption, which reduces OPEX

## Interfaces

<b>Ethernet Interface</b>	1 RJ-45 Ethernet interface (1 FE/GE)
<b>Power Supply</b>	PoE++ (IEEE 802.3bt compliant)
<b>Protocols Used</b>	IPv4/IPv6 (Dual Stack), UDP, TCP, ICMP, SNMPv2c, NTP, SSH, IPsec, TR-069, HTTP/HTTPS, 1588v2, DHCP
<b>Network Management</b>	IPv4/IPv6, HTTP/HTTPS, SNMPv2c, TR-069, SSH
<b>VLAN/VxLAN</b>	802.1Q/VxLAN
<b>LED Indicators</b>	4 x status LED CELL1/CELL2/ALM/PWR

## Performances

<b>Peak Data Rate (DC)</b>	<b>2x20 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	2x105	2x85
	UL/DL Config 2	2x145	2x14
	UL/DL Config 6	2x85	2x35
	<b>2x10 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	2x51	2x14
	UL/DL Config 2	2x70	2x7
	UL/DL Config 6	2x42	2x17
<b>Peak Data Rate (CA)</b>	<b>2x20 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	210	56
	UL/DL Config 2	290	28
	UL/DL Config 6	170	70
	<b>2x10 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	102	28
	UL/DL Config 2	140	14
	UL/DL Config 6	84	34
	<b>20 MHz + 10 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	156	42
	UL/DL Config 2	215	21
	UL/DL Config 6	127	52
	<b>20 MHz + 15 MHz</b>	<b>DL (Mbps)</b>	<b>UL (Mbps)</b>
	UL/DL Config 1	182	49
	UL/DL Config 2	250	24
	UL/DL Config 6	148	61
<b>User Capacity</b>	UL/DL Config 6		<ul style="list-style-type: none"> <li>• SC/CA: 96 RRC connected users</li> <li>• DC: 96+96 RRC connected users</li> </ul>
<b>Maximum Deployment Range</b>	5 kilometers		
<b>Latency</b>	30 milliseconds		
<b>Receive Sensitivity</b>	-100 dBm (per channel)		
<b>Modulation</b>	MCS0 (QPSK) to MCS27 (256QAM) DL: QPSK, 16QAM, 64QAM, 256QAM UL: QPSK, 16QAM, 64QAM		
<b>Transmit Power Range</b>	0 to 24 dBm per channel (combined +30 dBm, configurable) (1 dB interval)		
<b>Quality of Service</b>	Nine-level priority indicated by QoS Class Identifiers (QCI)		
<b>ARQ/HARQ</b>	Yes		
<b>Synchronization</b>	GPS, 1588v2		

## Modulation Levels (Adaptive)

MCS	Modulation Scheme	RSRP (dBm)	RSRP (dBm)
0-4	QPSK	$-120 \leq \text{RSRP} < -110$	$4 < D \leq 5$
5-9	16 QAM	$-110 \leq \text{RSRP} < -100$	$3 < D \leq 4$
10-19	64 QAM	$-100 \leq \text{RSRP} < -85$	$2 < D \leq 3$
20-27	256 QAM	$\text{RSRP} \geq -85$	$D \leq 2$

NOTE: The information provided is for reference only as the environment can impact modulation levels.  
Scenario: Base Station height is 30 meters; Customer User Equipment (CPE) height is two meters.

## Features

<b>Voice</b>	VoLTE*
<b>NSA</b>	Supported
<b>Traffic Offload</b>	Local breakout
<b>Layer 2 Support</b>	Transparent Bridge Mode
<b>Maintenance</b>	<ul style="list-style-type: none"> <li>• Local/Remote Web maintenance</li> <li>• Online status management</li> <li>• Performance statistics</li> <li>• Fault management</li> <li>• Local/Remote software upgrade</li> <li>• Logging</li> <li>• Connectivity diagnosis</li> <li>• Automatic start and configuration</li> <li>• Alarm reporting</li> <li>• User information tracing</li> <li>• Signaling trace</li> </ul>

\* Planned for future release.

## Link Budget

<b>Antenna Connection</b>	N-Type connector for external high-gain antenna
<b>GPS Antenna</b>	External GPS antenna, N-Type connector
<b>Power Control</b>	UL Open-loop/Closed-loop Power Control, DL Power Allocation (3GPP TS 36.213 compliant)

## Physical

<b>Surge Suppression</b>	VoLTE*
<b>Power Interface Lightning Protection</b>	Supported
<b>MTBF</b>	Local breakout
<b>MTTR</b>	Transparent Bridge Mode
<b>Ingress Protection Rating</b>	IP65
<b>Operating Temperature</b>	-40°F to 131°F / -40°C to 55°C
<b>Storage Temperature</b>	-58°F to 149°F / -50°C to 65°C
<b>Humidity</b>	5% to 95% RH
<b>Atmospheric Pressure</b>	70 kPa to 106 kPa
<b>Power Consumption</b>	Typical 20W, maximum 25W
<b>Weight</b>	With pre-installed bracket: 10.5 lb/4.75 kg Without bracket: 9.6 lb/4.35 kg
<b>Dimensions (HxWxD)</b>	With joint: <ul style="list-style-type: none"> <li>• 15.0 x 8.9 x 3.0 inches</li> <li>• 381 x 227 x 75millimeters</li> </ul> Without joint and handle: <ul style="list-style-type: none"> <li>• 12.2 x 8.9 x 3.0 inches</li> <li>• 311 x 227 x 75millimeters</li> </ul>
<b>Installation</b>	Pole or wall mount

## Global Part Numbers

<b>P5G-APO101</b>	LTE101 Indoor/Outdoor TDD Access Point – LTE Release 15, 4x250mW(24 dBm), 1FE/GE, PoE++, 3.5 GHz (3550MHz–3700MHz), B48, external antenna <ul style="list-style-type: none"> <li>• FCC certification: 2AG32PBS3101SE</li> <li>• IC certification: 20982-PBS3101SE</li> </ul>
-------------------	--