



RAPID SEAL #20-146 Black

A durable black sealant that forms a protective skin that is both tough and flexible. Seals cracks, resists rust and corrosion, and blocks moisture. Can be used in a variety of applications---seal leaky gutters, rustproof the underbody of a car, prune a tree. Dries fast, does not sag, and can be topcoated.

Suggested Uses:

Roof areas:
 Skylights
 Flashings
 Gutters
 Antenna installations
 Small cracks/holes in driveways
 Tree/Shrub pruning

Packaging:

UPC Code	043281004671
Cans per case	12
Shipping weight per case	18 lbs.
Container	20 fluid ounce can
Label weight	18 ounces (511 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	60%
MIR value	Does not exceed 1.40
California Compliancy	Does not exceed 1.60
HAPs content	18%
Storage Temperature	40-90F
Application Temperature	50-100F
Heat Resistance	300F
Gasoline Resistance	No
Resin System	Petroleum Asphalt
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To handle	4-6 hours

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Low Lustre, 15-25

*as measured on a 60 degree gloss meter

11-27-2021