

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Log Jam
Product code : Not available

1.2. Recommended use and restrictions on use

Recommended use : Caulking

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the OSHA requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, SDS or both in accordance with applicable government regulations

1.3. Supplier

Supplier

Sashco Inc.
14802 Grant St.
Thornton, CO, 80023
USA
T 800-767-5656
info@sashco.com

1.4. Emergency telephone number

Emergency number : 800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Eye Irrit. 2A
STOT RE 2

Causes serious eye irritation
May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Causes serious eye irritation
May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary statements (GHS US) :

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Do not breathe fume, spray, vapors.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Get medical advice/attention if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|--------------------------------|---------------------|---------|
| Limestone | CAS-No.: 1317-65-3 | 15 - 45 |
| Ethylene glycol | CAS-No.: 107-21-1 | 1 – 5 |
| Titanium Dioxide | CAS-No.: 13463-67-7 | 1 – 5 |
| Calcium oxide | CAS-No.: 1305-78-8 | 0.1 < 1 |
| Sodium dodecylbenzenesulfonate | CAS-No.: 25155-30-0 | 0.1 < 1 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Get medical advice/attention if you feel unwell. |
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| First-aid measures after skin contact | : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. |
| Symptoms/effects after skin contact | : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic symptoms | : May cause damage to organs through prolonged or repeated exposure. |

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : Direct water spray may cause frothing.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe fume, spray, vapors. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed.

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Log Jam | |
|---|--|
| No additional information available | |
| Sodium dodecylbenzenesulfonate (25155-30-0) | |
| No additional information available | |
| Limestone (1317-65-3) | |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Calcium oxide (1305-78-8) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 2 mg/m ³ |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL (TWA) [1] | 5 mg/m ³ |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH | 25 mg/m ³ |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 2 mg/m ³ |
| Ethylene glycol (107-21-1) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 25 ppm (vapor fraction) |
| ACGIH OEL STEL | 10 mg/m ³ (inhalable particulate matter, aerosol only) |
| ACGIH OEL STEL [ppm] | 50 ppm (vapor fraction) |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| Titanium Dioxide (13463-67-7) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Titanium dioxide |
| ACGIH OEL TWA | 0.2 mg/m ³ (nanoscale respirable particulate matter) 2.5 mg/m ³ (finescale respirable particulate matter) |
| Remark (ACGIH) | TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) |
| ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| Regulatory reference | ACGIH 2020 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Titanium dioxide (Total dust) |

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Titanium Dioxide (13463-67-7) | |
|--|---|
| OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH | 5000 mg/m ³ |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale) |

Exposure limit values of other components

| Formaldehyde (50-00-0) | |
|---|--|
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL (TWA) [2] | 0.75 ppm |
| OSHA PEL (STEL) [2] | 2 ppm (see 29 CFR 1910.1048) |
| Remark (OSHA) | Formaldehyde is subject to the standard 29 CFR 1910.1048, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements. |

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

| |
|---|
| Hand protection: |
| Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness. |
| Eye protection: |
| Wear eye/face protection |
| Skin and body protection: |
| Wear suitable protective clothing |
| Respiratory protection: |
| In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment. |

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Viscous paste, textured.
- Color : Various

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| | |
|---|-----------------------------|
| Odor | : Slight Ammonia. |
| Odor threshold | : No data available |
| pH | : 9 |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 212 °F (100 °C) |
| Flash point | : Not applicable |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not flammable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20°C | : No data available |
| Relative density | : 1.03 |
| Density | : 1.03 g/cm ³ |
| Solubility | : Negligible. |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : 178000 mm ² /s |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|-------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified. |

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Sodium dodecylbenzenesulfonate (25155-30-0) | |
|--|--|
| LD50 oral rat | 500 mg/kg |
| LC50 inhalation rat | 310 mg/m ³ (Exposure time: 4 h) |
| ATE US (oral) | 500 mg/kg body weight |
| ATE US (gases) | 100 ppmV/4h |
| ATE US (vapors) | 0.31 mg/l/4h |
| ATE US (dust, mist) | 0.31 mg/l/4h |
| Calcium oxide (1305-78-8) | |
| LD50 oral rat | 500 mg/kg |
| LC50 inhalation rat | > 6.04 mg/l/4h |
| ATE US (oral) | 500 mg/kg body weight |
| Ethylene glycol (107-21-1) | |
| LD50 oral rat | 4700 mg/kg |
| LD50 dermal rat | 10600 mg/kg |
| LC50 inhalation rat | > 2.5 mg/l (Exposure time: 6 h) |
| ATE US (oral) | 500 mg/kg body weight |
| Titanium Dioxide (13463-67-7) | |
| LD50 oral rat | > 10000 mg/kg |

| | |
|-------------------------------------|---|
| Skin corrosion/irritation | : Not classified. pH: 9 |
| Serious eye damage/irritation | : Causes serious eye irritation. pH: 9 |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified. |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral). |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : 178000 mm ² /s |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. |
| Symptoms/effects after skin contact | : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic symptoms | : May cause damage to organs through prolonged or repeated exposure. |
| Other information | : Likely routes of exposure: ingestion, inhalation, skin and eye. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|---|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|---|

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : The generation of waste should be avoided or minimized wherever possible. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Formaldehyde, which is known to the State of California to cause cancer, and Ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information


according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 08/28/2015
Revision date : 08/30/2024
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



| Full text of H-phrases | |
|------------------------|---|
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| STOT SE 1 | Specific target organ toxicity (single exposure) Category 1 |

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating
Health : 2 Moderate Hazard - Temporary or minor injury may occur
Health : * - Chronic (long-term) health effects may result from repeated overexposure
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection : A - Safety glasses

Log Jam

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Indication of changes: | | | |
|------------------------|-----------------------|----------|-------------|
| Section | Changed item | Change | Comments |
| 2 | GHS-US classification | Modified | Version 3.1 |
| SDS | SDS update | Modified | Version 3.1 |
| 14 | Transport information | Modified | Version 3.2 |

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.