

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Slime Tube Sealant  
Product code : 100042, 10003, 10004, 10056W, 10058, 10162, 10186, SB-275G, SB-55G-AMI, 30010, 30011, 30012, 30013, 30014, 30015, 30043, 30044, 30045, 30047, 30049, 30051, 30070, 30074, 30075, 30076, 30079, 30081, 30084, 30085, 30086, 30088

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Tire sealant  
Restrictions on use : No additional information available

#### 1.3. Supplier

##### Supplier

ITW Global Tire Repair, Inc.  
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401, USA  
Tel: (888) 457-5463 (Toll Free)

#### 1.4. Emergency telephone number

Emergency number : Chemtel: +1(813)248-0585 (International)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction  
Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction  
Precautionary statements (GHS US) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.  
P261 - Avoid breathing vapors.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves.  
P302+P352 - If on skin: Wash with plenty of soap and water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Glycerol	CAS-No.: 56-81-5	≥ 25 – < 40	Not classified
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	CAS-No.: 4719-04-4	≥ 0.1 – < 0.25	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Magnesium oxide	CAS-No.: 1309-48-4	≥ 0.05 – < 0.1	Not classified
Titanium dioxide	CAS-No.: 13463-67-7	≥ 0.02 – < 0.05	Carc. 2, H351
Quartz (SiO <sub>2</sub> )	CAS-No.: 14808-60-7	≥ 0.02 – < 0.05	Carc. 1A, H350
Carbon black	CAS-No.: 1333-86-4	≥ 0.0015 – < 0.02	Carc. 2, H351
Acetaldehyde	CAS-No.: 75-07-0	≥ 0.0015 – < 0.02	Flam. Liq. 1, H224 Eye Irrit. 2A, H319 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off contaminated clothing. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Redness. Lacrimation. Itching. Blurred vision.  
Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting. Abdominal pain.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Alcohol-resistant foam. Carbon dioxide. Water spray. Use extinguishing agent suitable for surrounding fire.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : In case of fire and/or explosion do not breathe fumes. Burning produces stinking and toxic fumes. Heating will cause a rise in pressure with a risk of bursting.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all contact with skin, eyes, or clothing.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Do not touch or walk on the spilled product. No action shall be taken without appropriate training or involving any personal risk.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak, if possible without risk. Do not touch or walk on the spilled product. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up	: Caution : this product can cause the floor to be slippery. Move containers from spill area. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean contaminated surfaces with an excess of water. Prevent entry to sewers and public waters.
Other information	: Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Provide adequate ventilation to minimize dust and/or vapor concentrations. Avoid breathing vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid release to the environment. Empty containers retain product residue and can be hazardous.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep away from food, drink and animal feedingstuffs. Store in a dry place. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Keep only in original container. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store in accordance with local, regional, national or international regulation.
Incompatible materials	: Direct sunlight. Heat sources.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Slime Tube Sealant</b>	
No additional information available	
<b>Glycerol (56-81-5)</b>	
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Quartz (SiO<sub>2</sub>) (14808-60-7)</b>	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Magnesium oxide
ACGIH OEL TWA	10 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT; metal fume fever. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Magnesium oxide fume - Total Particulate
OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)	
No additional information available	
Titanium dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	0.2 mg/m <sup>3</sup> (Nanoscale particles. R - Repairable particulate matter) 2.5 mg/m <sup>3</sup> (Finescale particles. R - Repairable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Carbon black (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black
OSHA PEL (TWA) [1]	3.5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Acetaldehyde (75-07-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetaldehyde
ACGIH OEL Ceiling [ppm]	25 ppm

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetaldehyde (75-07-0)	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Acetaldehyde
OSHA PEL (TWA) [1]	360 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Avoid all unnecessary exposure.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

<b>Hand protection:</b>
Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer
<b>Eye protection:</b>
Use splash goggles when eye contact due to splashing is possible
<b>Skin and body protection:</b>
Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Green

Odor : No data available

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability : No data available

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization: Will not occur.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Glycerol (56-81-5)	
LD50 oral rat	12600 mg/kg

  

Quartz (SiO <sub>2</sub> ) (14808-60-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)	
ATE US (oral)	500 mg/kg body weight
Acetaldehyde (75-07-0)	
LD50 oral rat	661 g/kg
LD50 dermal rabbit	3540 mg/kg
LC50 Inhalation - Rat	13300 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Acetaldehyde (75-07-0)	
IARC group	2B - Possibly carcinogenic to humans, 1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Acetaldehyde (75-07-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Rednesses. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact	: Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Abdominal pain.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Do not allow product to spread into the environment.

Acetaldehyde (75-07-0)	
LC50 - Fish [1]	30.8 mg/l (96 h, Pimephales promelas)
EC50 - Crustacea [1]	48.3 mg/l (48 h, Daphnia magna)
EC50 - Other aquatic organisms [1]	237 – 249 mg/l (120 h, Nitzschia linearis)

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetaldehyde (75-07-0)	
LC50 - Fish [2]	53 mg/l (96 h, Lepomis macrochirus)
EC50 - Crustacea [2]	9000 mg/l (48 h, Daphnia magna)
EC50 - Other aquatic organisms [2]	280.6 mg/l (5-15-25 min., Photobacterium phosphoreum)

### 12.2. Persistence and degradability

Slime Tube Sealant	
Persistence and degradability	Biodegradability in water: no data available.

### 12.3. Bioaccumulative potential

Slime Tube Sealant	
Bioaccumulative potential	No data available concerning bioaccumulation.

### 12.4. Mobility in soil

Slime Tube Sealant	
Ecology - soil	No additional information available.

### 12.5. Other adverse effects

Other adverse effects : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not dispose of the packaging without first carrying out the necessary cleaning.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

**TDG**  
Transport hazard class(es) (TDG) : Not applicable

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### IMDG

Transport hazard class(es) (IMDG) : Not applicable

### IATA

Transport hazard class(es) (IATA) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

No data available

#### TDG

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Glycerol	CAS-No. 56-81-5	≥ 25 – < 40%
Quartz (SiO <sub>2</sub> )	CAS-No. 14808-60-7	≥ 0.02 – < 0.05%
Magnesium oxide	CAS-No. 1309-48-4	≥ 0.05 – < 0.1%
2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	CAS-No. 4719-04-4	≥ 0.1 – < 0.25%
Titanium dioxide	CAS-No. 13463-67-7	≥ 0.02 – < 0.05%
Carbon black	CAS-No. 1333-86-4	≥ 0.0015 – < 0.02%
Acetaldehyde	CAS-No. 75-07-0	≥ 0.0015 – < 0.02%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Acetaldehyde	CAS-No. 75-07-0	≥ 0.0015 – < 0.02%
--------------	-----------------	--------------------

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Acetaldehyde (75-07-0)</b>	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb

### 15.2. International regulations

#### CANADA

<b>Glycerol (56-81-5)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Quartz (SiO<sub>2</sub>) (14808-60-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Magnesium oxide (1309-48-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Titanium dioxide (13463-67-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Carbon black (1333-86-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Acetaldehyde (75-07-0)</b>
Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

<b>Slime Tube Sealant</b>
Not listed on the United States TSCA (Toxic Substances Control Act) inventory

<b>Glycerol (56-81-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)

<b>Quartz (SiO<sub>2</sub>) (14808-60-7)</b>
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Magnesium oxide (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol (4719-04-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Titanium dioxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.3. US State regulations

 **WARNING:** This product can expose you to Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/29/2023  
Data sources : ECHA (European Chemicals Agency). Supplier's safety documents.  
Training advice : Training staff on good practice.

### Full text of H-phrases

H224	Extremely flammable liquid and vapor
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer

# Slime Tube Sealant

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

<b>Indication of changes:</b>
-------------------------------

1.1. Product identifier.
--------------------------

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.