



Notes:

1. A symbol "△" means "Key control" dimensions;
2. A symbol "Ⓜ" will be next to any dimensions view or note which has been modified with the current drawing revision;
3. RoHs compliant ;
4. Operating temperature: 0°C~70°C ;
5. 100% bit error test and performance test;
6. Electrical and mechanical performance shall meet SFF-8431;

Table 1

Item	L (Unit: M)	Tolerance (Unit: CM)
1	≤1	+5/-0
2	1<L≤4.5	+15/-0
3	4.5<L≤14.5	+30/-0
4	≥14.5	+2%/-0

2019-4-17	Rex-Yu	New drawing	A0
date	signature	Discription	Version

7					
6					
5	82050005	A0	Module protector, material is PVC	pcs	2
4	83020010	A0	25*11mm module label, white	pcs	2
3		A0	SFP+ 10G OM3 LSZH optical cable, aqua	pcs	1
2	22020001	A0	SFP+ 10G AOC PCBA	pcs	2
1	23020004	A0	SFP+ 10G AOC shell, black pull tab	set	2
Item	PN	Version	Discription	Unit	Quantity
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCE ARE: DECIMALS			CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		
Unit: mm		ANGLES ±1/2			
THE FIRST VIEW			APPROVALS / DATE		
MATERIAL:			DESIGNED Rex-Yu/2019-4-17		
SURFACE AND COLOR:			CHECKED		
CUSTOMER CODE:			APPROVED		
TITLE:			10G SFP+ AOC(OM3)		
SIZE A4	PART NO: AOC-SFP-10G-xxxM		REV. A0		
SCALE: 1:1	CAD FILE:	SHEET: 1 OF 1			