



Silent+ Mini Aqua

The product packaging for the Silent+ Mini Aqua pump is shown, featuring the Aspen Pumps logo and the text "The World's Quietest Mini Pump Universal for all Mini-Splits #1 Mini Pump in North America Low Maintenance. No Call Backs". The packaging also highlights "REVOLUTIONIZING MINI PUMPS" and "The First with Variable Speed Technology". To the right of the packaging is a blue, sleek, and slender condensate removal pump. A QR code is located in the top right corner of the packaging.

FP3420/MG
Condensate
Removal Pump

Key Features:

- Fits neatly into trunking and inside mini split units
- Sleek and slender profile
- Adaptive variable speed flow with intelligent capacitance sensing
- As low as 16dB(A)*
- 3-year warranty

Range Suitability:

- 40kW / 136,000BTU/h / 11.37 tons
- Ducted units, Floor standing and chassis units, Ductless mini split systems
- Perfect for- smaller commercial and residential applications where quiet is needed

In the Box:

- Silent+ Mini Aqua 5th Gen Pump
- Reservoir (incl. filter and lid)
- 5' (1.5m) Plug and Play Cable**
- 5' (1.5m) Clear PVC Tube
- 6" (152mm) Clear Vent Hose
- 8.5" (220mm) Blue Inlet Hose
- Drain connector kit: Straight connector and rubber elbow
- Fixing Pad
- Quick Start Guide

Product Specifications:

Max. flow	9.25 US Gallons (35L/h) @ 0m head
Max. rec. head	33ft./10m
Max. suction lift	6'/1.5m
Min. dB(A) @ 1m	16dB(A)*
Power supply	100-250V, 50/60Hz, 0.18A, 2.4W
Rated	Continuous
Class	II
Max. unit output	40kW / 136,000BTU/h / 11.37 tons
Max. ambient temp	104°F (40°C)
IP Protection	IP24
Inlet o/d	5/8" (16mm)
Outlet o/d	1/4" (Ø6mm)
Safety switch	High level safety wires N.C. contacts, 250 VAC, 3A max
Self priming	✓

*Assuming solid wall construction with a 2kW unit.

**Not backwards compatible

Ensure ALL cleaning chemicals are flushed out of the reservoir after use.

Silent+ Mini Aqua | 100-250VAC, 50Hz/60Hz

