

IT'S WARRIOR TIME – WW-722 IS NEW AND IMPROVED

SELECT

722 Series

WarriorWrap Select Vinyl (mid-grade) Electrical Tape has been reformulated to provide superior performance. 90% of the raw materials have been changed. The new film is softer and more flexible to help prevent splitting. The PVC film and glue formulas were both updated to have better balance between room temperature and cold temperature performance.

Key Takeways

- Room Temp 73°F** The Improved WW-722 adhesion is comparable to 3M 1700 and better balanced than the Original WW-722.
- Freezing 32°F** The Improved WW-722 almost doubled the adhesion of the Original WW-722.
- Sub-freezing 14°F** The Improved WW-722 adhesion to steel is almost 4x higher than the competition.



Excellent adhesion and elasticity



Highly resistant to abrasion and corrosion



176°F (80°C) maximum temperature



7 mil thickness



UL 510 Listed



CSA Standard C22.2



Flame-retardant

WW-722 Series Test Data

Test Item	Unit	Original WW-722	Improved WW-722	3M 1700
Total Thickness	mil	7	7	7
Adhesion to Steel at 23°C, 73°F	oz/in	25	22	22
Adhesion to Steel at 0°C, 32°F	oz/in	15	28	37
Adhesion to Steel at -10°C, 14°F	oz/in	3	23	6