



PBE PROFESSIONAL TRIM PAINTS

Seymour PBE Professional Trim paint is formulated using an acrylic resin that resists fading from ultraviolet light and degradation from chemicals. Spray like a professional without the equipment, prep time, cleanup, or waste. Several light coats produce a better finish than one heavy coat. A heavy coat applied over an enamel may cause lifting. Bare surfaces or rusted metal surfaces should first be primed with the PBE sandable primers.

Suggested Uses:

body panels
 engine parts
 metal structures
 aviation parts
 heavy machinery

Packaging:

Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint/lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.78
Solids Content	7%
HAPs content	25%
Storage Temperature	40-100F
Application Temperature	50-90F
Abrasion Resistance	Fair
MIR value	Non-flats <0.95 Flat <0.80
Heat Resistance	250F continuous
Resin System	Acrylic lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To Topcoat	15 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*:	High Gloss, >80
	Flat, <5
	Semi-Gloss, 25-35

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
20-1677	Trim Gloss Black	043281002257
20-1678	Trim Flat Black	043281002264
20-1679	Trim Semi-Gloss Black	043281002141

12-1-2021