

Notes:

- 1.A symbol“△” means "Key control" dimension;
- 2.A symbol“⊗” will be next to any dimensions view or note which has been modified with the current drawing revision;
- 3.RoHs compliant ;
- 4.Oprating temperature:0°C~70°C ;
- 5.100% bit error test and performance shall;
- 6.Electrical and mechanical performance shall meet SFF-8436;




Table 1

Item	L (Unit: M)	Tolerance (Unit: OM)
1	≤1	+5/-0
2	1<L≤4.5	+15/-0
3	4.5<L≤14.5	+30/-0
4	≥14.5	+2%/ -0

2020-03-31	Rex-Yu	update table 1	A2
2019-10-30	Rex-Yu	update table 1	A1
2019-4-17	Rex-Yu	new release	A0
date	signature	Description	Version

5	82050006		black dust protector	pcs	2
4			100G QSFP28 MT-MT OM3 optical cable	pcs	1
3	83020824		white module label	pcs	2
2	23020003		100G QSFP+ AOC shell	set	2
1	22020004		100G QSFP28 AOC PCBA	pcs	2
Item	PN	Version	Description	Unit	Quantity

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCE ARE: DECIMALS	ANGLES ±1/2	CAD GENERATED DRAWING. DO NOT MANUALLY UPDATE	
		THE FIRST VIEW	
APPROVALS / DATE			
DESIGNED Rex-Yu/2020-03-31			
MATERIAL:		CHECKED Rex-Yu/2020-03-31	TITLE: 100G QSFP28 AOC (OM3)
SURFACE AND COLOR:		APPROVED YuanlinDen/2020-03-31	PART NO: AOC-QSFP28-100G-xxxM
CUSTOMER:			REV. A2
			SCALE: 1:1
			CAD FILE:
			SHEET: 1 OF 1