

NSI INDUSTRIES LLC
 EASY-TWIST™ DRUM LABEL
 WWC-B-D_ET-TOWC_Pack-
 aging_Label
 v2
 238mm x 95.25mm
 06/2024

DO NOT PRINT CYAN
 LINE-PLACEMENT ONLY



The colors on the package are CMYK, but they should match the spot colors shown above.

95.25mm

WARNING/PRECAUTION/ADVERTISSEMENT

WWC-B-D


Turn off power before installing or removing connectors
 Couper l'alimentation avant d'installer ou de retirer les raccords / Apague la alimentación antes de instalar o retirar los conectores

**TO BE SOLD ONLY WITH
 INSTALLATION INSTRUCTIONS**

INSTRUCTIONS
 Strip wires 7/8" (22.2 mm)
 Pre-twisting unnecessary, hold stripped wires together with ends even. Lead stranded wires slightly
 Align any frayed strands or conductors
 Push wires into connector and screw on until two twists are visible in wires

SPECIFICATIONS
 Listed as a pressure-type wire connector
 Temperature Rating: 105°C (221°F) max
 Voltage Rating: 600V max building wiring; 1000V max in signs or luminaires
FOR USE WITH COPPER TO COPPER CONDUCTOR

▲ **WARNING:** Cancer and reproductive harm
 ▲ **ADVERTENCIA:** Cáncer y daño reproductivo
 ▲ **ADVERTISSEMENT:** Cancer et troubles de l'appareil reproducteur - www.P65Warnings.ca.gov.




EASY-TWIST®

WINGED WIRE CONNECTORS

Blue Winged Connectors

Raccords Ailes Bleu
 Conectores Azules Con Clip
 De Seguridad



9,500

Qty/Qte/Ctd

14-6 AWG

Solid & Stranded

**WIRE COMBINATIONS*
 For UL Listed and CQC Certified**
 1 or 2 #6
 2 #8
 2 to 4 #10
 3 #12


For CSA and CQC Certified
 2 or 3 #8
 2 to 4 #10
 1 #8 w/1 to 3 #10
 1 or 2 #8 w/1 to 3 #12

SPÉCIFICATIONS
 Répertoire comme un connecteur de fil de type à pression
 Température nominale : 105°C (221°F) max
 Tension nominale : 600V max. pour le câblage des bâtiments ; 1000V max. pour les luminaires et les panneaux
 À UTILISER AVEC UN CONDUCTEUR CUIVRE À CUIVRE

INSTRUCCIONES
 1. Desforre los cables 7/8" (22.2 mm)
 2.No es necesario que estén previamente trenzados, sostenga los cables desforrados juntos con las puntas al mismo nivel. Meta un poco los cables trenzados
 3. Alinee los cables trenzados o conductores deshilachados
 4. Introduzca los cables en el conector y enrosque hasta que se vean dos trenzas en los cables


ESPECIFICACIONES
 Certificado como conector de cables tipo a presión
 Temperatura nominal: 105 °C (221 °F) máx.
 Voltaje nominal: 600 V máximo en el cableado del edificio; 1000 V máximo en artefactos y letreros
PARA USARSE CON CONDUCTORES DE COBRE A COBRE

*For complete listing of wire combinations and voltage ratings, scan QR code or contact Customer Service at 800-321-5847




NSI Industries
 800.321.5847
nsiindustries.com


Made in Taiwan
 Fabrique en Taiwan
 Hecho en Taiwán




SCAN ME




LISTED
 WIRE CONNECTORS
 E158007
 8100



RoHS
 COMPLIANT



REACH
 COMPLIANT



6 62381 14007 4

238mm