

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name** NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER  
**Synonyms** NOX CRETE SILCOSEAL CLASSIC BOND BREAKER • NOXSILCOCLASS20, NOXSILCOCLASS200 - PRODUCT CODE(S)

### 1.2 Uses and uses advised against

**Uses** BOND BREAKER • INDUSTRIAL APPLICATIONS

### 1.3 Details of the supplier of the product

**Supplier name** RAMSETREID (A DIVISION OF ITW AUSTRALIA PTY LTD) (REID)  
**Address** 1 Ramset Drive, Chimside Park , VIC, 3116, AUSTRALIA  
**Telephone** 1300 780 063  
**Email** [enquiry@ramset.com.au](mailto:enquiry@ramset.com.au)  
**Website** <http://www.reid.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 1800 033 111

### 1.7 Details of alternative suppliers of the product

**Supplier name** NOX-CRETE MANUFACTURING INC  
1444 South 20th Street, Omaha, NE, 68108, UNITED STATES  
Phone: 402-341-2080  
Emergency: 402-341-2080 · (800) 424-9300  
[corporate@nox-crete.com](mailto:corporate@nox-crete.com)  
[www.nox-crete.com](http://www.nox-crete.com)

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Flammable Liquids: Category 3

#### Health Hazards

Aspiration Hazard: Category 1  
Skin Corrosion/Irritation: Category 2  
Serious Eye Damage / Eye Irritation: Category 1  
Acute Toxicity: Inhalation: Category 4  
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)  
Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)  
Carcinogenicity: Category 2  
Toxic to Reproduction: Category 1A  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

#### Environmental Hazards

Aquatic Toxicity (Chronic): Category 3

### 2.2 GHS Label elements

**PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER****Signal word DANGER****Pictograms****Hazard statements**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H360 May damage fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

**Prevention statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

**Response statements**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P310 Immediately call a POISON CENTRE or doctor/physician.  
P321 Specific treatment is advised - see first aid instructions.  
P331 Do NOT induce vomiting.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use appropriate media to extinguish.

**Storage statements**

P403 + P233 + P235 Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
P405 Store locked up.

**Disposal statements**

P501 Dispose of contents/container in accordance with relevant regulations.

**2.3 Other hazards**

No information provided.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
TOLUENE	108-88-3	203-625-9	<11%
ALCOHOL(S)	-	-	<10%
1,2,4-TRIMETHYLBENZENE	95-63-6	202-436-9	<6%
XYLENE	1330-20-7	215-535-7	<2%
CUMENE (ISOPROPYL BENZENE)	98-82-8	202-704-5	<1%

**PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER**

ETHYLBENZENE	100-41-4	202-849-4	<1%
HYDROTREATED PETROLEUM DISTILLATE	-	-	>60%
ADDITIVE(S)	-	-	Remainder

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>First aid facilities</b>	Eye wash facilities and safety shower should be available.

**4.2 Most important symptoms and effects, both acute and delayed**

May damage fertility or the unborn child. Repeated exposure to toluene may result in central nervous system (CNS), liver and kidney damage.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

**5.2 Special hazards arising from the substance or mixture**

Flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

- 3Y
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

## PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation and fire protection systems.

### 7.3 Specific end uses

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
1,2,4-Trimethylbenzene (as Trimethyl benzene)	SWA [AUS]	25	123	--	--
Cumene	SWA [AUS]	25	125	75	375
Cumene	SWA [Proposed]	0.1	0.5	--	--
Ethyl benzene	SWA [AUS]	100	434	125	543
Ethyl benzene	SWA [Proposed]	20	87	--	--
Mineral Oil Mist	SWA [AUS]	--	5	--	--
Toluene	SWA [AUS]	50	191	150	574
Toluene	SWA [Proposed]	20	75	--	--
Trimethylbenzene (all isomers)	SWA [Proposed]	20	100	--	--
Xylene	SWA [AUS]	80	350	150	655

#### Biological limits

Ingredient	Determinant	Sampling Time	BEI
ETHYLBENZENE	Sum of mandelic acid and phenylglyoxylic acid in urine	End of shift	0.15 g/g creatinine
TOLUENE	o-Cresol in urine (with hydrolysis)	End of shift	0.3 mg/g creatinine
	Toluene in urine	End of shift	0.03 mg/L
	Toluene in blood	Prior to last shift of workweek	0.02 mg/L
XYLENE	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine

Reference: ACGIH Biological Exposure Indices

### 8.2 Exposure controls

#### Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

#### PPE

- Eye / Face** Wear splash-proof goggles.
- Hands** Wear PVA or viton® gloves.
- Body** Wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator or an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	RED LIQUID
Odour	SLIGHT SOLVENT ODOUR
Flammability	FLAMMABLE
Flash point	24°C (cc)
Boiling point	94°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.81
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

### 9.2 Other information

VOC	< 700 g/L
-----	-----------

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization will not occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

### 10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity	Harmful if inhaled. Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.
----------------	---

**PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER****Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
TOLUENE	5580 mg/kg (rat)	5000 mg/kg (rabbit)	25.7 - 30 mg/L/4hrs (rat)
1,2,4-TRIMETHYLBENZENE	6000 mg/kg (rat)	--	18 g/m <sup>3</sup> /4hrs (rat)
XYLENE	> 2000 mg/kg (rat) (AICIS)	> 1700 mg/kg (rabbit)	5000 ppm (rat)
CUMENE (ISOPROPYL BENZENE)	1400 mg/kg (rat)	12300 ug/kg (rabbit)	24700 mg/m <sup>3</sup> /2H (mouse)
ETHYLBENZENE	3500 mg/kg (rat)	17800 mg/kg (rabbit)	17.8 mg/l/4 hours (rat)

<b>Skin</b>	Irritating to the skin. Contact may result in irritation, redness, rash and dermatitis.
<b>Eye</b>	Causes serious eye irritation. Contact may result in irritation, lacrimation, pain and redness.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Suspected of causing cancer. Ethylbenzene and cumene are classified as possibly carcinogenic to humans (IARC Group 2B).
<b>Reproductive</b>	Over exposure to toluene may damage fertility or the unborn child.
<b>STOT - single exposure</b>	Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness.
<b>STOT - repeated exposure</b>	Repeated exposure to toluene may result in central nervous system (CNS), liver and kidney damage.
<b>Aspiration</b>	Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

No information provided.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

**Waste disposal** Dispose of in accordance with advice from your State's Environmental Protection Authority.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

**CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**



**PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	1263	1263	1263
<b>14.2 Proper Shipping Name</b>	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
<b>14.3 Transport hazard class</b>	3	3	3
<b>14.4 Packing Group</b>	III	III	III

**14.5 Environmental hazards**

Not a Marine Pollutant.

**14.6 Special precautions for user**

Hazchem code ●3Y  
 GTEPG 3C1  
 EmS F-E, S-E

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
 All components are listed on AIIC, or are exempt.

**16. OTHER INFORMATION**

**Additional information** **PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**  
 The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**  
 It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PRODUCT NAME NOX-CRETE SILCOSEAL CLASSIC BOND BREAKER****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**