



<b>Backing:</b>	Polyethylene Film
<b>Adhesive:</b>	Synthetic Rubber
<b>Liner:</b>	N/A
<b>Colors:</b>	Yellow
<b>Specifications:</b>	Meets NFPA-701, Tested in Accordance to ASTM E84
<b>Standard Sizes:</b>	72mm x 55M, 96mm x 55M, 6" x 60YD

### Applications

- In the convention and entertainment industry, tape safely hides any cords, cables, and wires to create a cleaner visual appearance
- Deadened adhesive strip creates a "tunnel" where adhesive doesn't adhere to cables
- Reduces the hazards of exposed cords and cables during heavy foot traffic

### Features

### Benefits

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Polyethylene Film Backing</li> <li>• Synthetic Rubber Adhesive</li> </ul> | <ul style="list-style-type: none"> <li>• Conformable and flexible</li> <li>• Excellent durability and solvent resistance</li> <li>• Low elongation for consistent surface bond</li> <li>• Pinked Edge available for hand tearability</li> <li>• High tack for good quick stick</li> <li>• Excellent shear strength</li> <li>• Repositionable and clean removal from many surfaces</li> </ul> |
| <ul style="list-style-type: none"> <li>• Deadened adhesive in the center of the tape</li> </ul>                    | <ul style="list-style-type: none"> <li>• Prevents adhesive residue from contact with cords, cables, and wires</li> </ul>   |

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	7.0 mils	0.178 mm	ASTM D-1000
<b>Adhesion to Steel</b>	70 oz/in	7.66 N/cm	PSTC-101
<b>Adhesion to Backing</b>	30 oz/in	3.28 N/cm	PSTC-101
<b>Tensile Strength</b>	20 lb/in	35.03 N/cm	ASTM D-1000
<b>Permeance</b>	0.11 US Perms		ASTM F1249
<b>Application Temperature</b>	30 to 160 °F	-1 to 71 °C	
<b>Operating Temperature</b>	20 to 200 °F	-7 to 93 °C	
<b>Elongation</b>	85%		
<b>Flame Spread Index</b>	0		
<b>Smoke Developed Index</b>	30		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

\* Subject to availability and minimum order

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.