

## OE SHINY GALV

#16-842



A shiny galvanized coating that protects and matches new galvanized metal. Resists oxidation and eliminates the need for an aluminum topcoat. Excellent for restoration of chain link fences and guardrails. The dried paint film contains a minimum of 65% zinc. It is considered a sacrificial coating, and meets ASTM A780 performance specifications.

### Suggested Uses:

All vehicle bodies  
 Agricultural, mining and construction equipment  
 Piping, storage tanks  
 Bridges  
 Ships and marine equipment

### Packaging:

UPC Code	043281006934
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	13 ounces (369 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.87
Solids Content	18%
% Zinc in dried paint film	68%
MIR value	1.05, cannot exceed 1.25
HAPs content	15%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Very Good
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	Epoxy
Shelf life	Guaranteed for 2 years

### Dry Time\*:

To touch	5 minutes
To topcoat	20 minutes

\*At 72F, 50% humidity, 1.5 mil thickness

\*\*Curing/Recoat time is extended with multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <15\*

\*as measured on a 60 degree gloss meter

3-23-2022