

Safety Data Sheet

Date of issue: 01/14/2026

Revised On 01/14/2026

1 Identification of the substance and manufacturer

Trade name: CERAMIC COATING
Other means of identification
Product code: 0000200032
Article category
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification**Classification of the substance or mixture**

Aerosols 3 H229 Pressurized container: may burst if heated.

Additional information:

GHS Hazard pictograms Void
Signal word Warning
Hazard statements Pressurized container: may burst if heated.
Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not pierce or burn, even after use.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

3 Composition/information on ingredients**Chemical characterization: Mixtures**

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

115-10-6 dimethyl ether	10-15%
-------------------------	--------

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: No further relevant information available.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling
Storage requirements: Use only in well ventilated areas.
 Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
 Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEEL (USA) Long-term value: 1000 ppm

Hygienic protection: Wash hands after use.
 Do not eat or drink while working.
Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

(Contd. on page 2)

Safety Data Sheet

Date of issue: 01/14/2026

Revised On 01/14/2026

Trade name: CERAMIC COATING

(Contd. of page 1)

Hand protection: Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection: Not required.

9 Physical and chemical properties

Physical state: Aerosol
Odor: Aromatic
Odor threshold: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: 100 °C (212 °F)
Flammability:
Lower Explosion Limit: Not determined.
Upper Explosion Limit: Not determined.
Flash point: Not applicable, as aerosol.
Flammability (solid, gas):
Decomposition temperature: Not determined.
pH-value: Not determined.
Viscosity: Not determined.
Solubility: Not determined.
Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density: Not determined.
Particle characteristics: Not applicable.
Appearance: Aerosol.
Ignition temperature: Product is not self-igniting.
Danger of explosion: Not determined.
Water: 78.3 %
Evaporation rate: Not applicable.
Partition coefficient: n-octanol/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: No decomposition if used according to specifications.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****115-10-6 dimethyl ether**

Inhalative | LC50/4 h | 308 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number: UN1950
DOT: UN1950
DOT: Aerosols, non-flammable
ADR: 1950 AEROSOLS

(Contd. on page 3)

Safety Data Sheet

Date of issue: 01/14/2026

Revised On 01/14/2026

Trade name: CERAMIC COATING

(Contd. of page 2)

Transport hazard class(es):	
Class	2.2 Gases
Special marking (IATA):	
Packaging Group:	--
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act
(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List
(DSL): All ingredients are listed or exempted.

Consumer Product Safety
Commission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs