

WW-RSL SERIES

LINERED RUBBER SPLICING TAPE - 600V

DESCRIPTION	FEATURES		
WW-RSL is a 30 mil (0.76mm) self-amalgamating, low-voltage rubber tape which is UL-510 Listed for use as primary insulation up to 600 volts. It easily conforms to irregular shapes and surfaces, yielding a void-free electrically-stable build up. WW-RSL is compatible with all extruded dielectric cable insulations and meets the ASTM D-4388 Type 1 standard.	Self-amalgamating Good electrical properties Good conformability Rated up to 600V Linered		

	BACKING	ADHESIVE	COLOR	STANDARD SIZES (WIDTH X LENGTH)	PART NUMBERS
MATERIALS	Rubber	None	Black	.75" x 22' (19mm x 6.7m) 1" x 22' (25mm x 6.7m) 1.5" x 22' (38mm x 6.7m) 2" x 22' (51mm x 6.7m)	WW-RSL-75 WW-RSL-10 WW-RSL-15 WW-RSL-20
	CHARACTERISTIC	TYPICAL VALUE		TEST METHOD	
TECHNICAL PROPERTIES	Thickness (mils)	30		UL 510	
	Tensile strength (psi)	435.11		UL 510	
	Elongation (%)	500		UL 510	
	Flammability	Pass		UL 510	
	Operating temp.: Continuous	176°F, 80°C		UL 510	
	Weather resistance	Pass		UL 510	
	Dielectric strength (V/mil)	508		UL 510	

RECOMMENDED USES	STORAGE	SHELF LIFE
For insulating of splices on solid dielectric cable through 600 volts in conjunction with a jacketing tape.	In original packaging, placed in a horizontal position, covered, between 5°C and 35°C.	24 months from date of manufacture.

Data in table represents average test results and are not to be used for specification purpose. Users should test the products' suitability for their intended use themselves.

LIMITED WARRANTY: NSI Industries LLC warrants that each of its products will be free from material and manufacture defects at the date of shipment (unless specified otherwise). NSI Industries LLC makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for their/fits intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proven to be defective, NSI Industries sole obligation and buyer's exclusive remedy shall be through the distributor, at NSI Industries' discretion, to replace, repair, or refund the product proved to be defective within the time period specified above. EXCEPT AS EXPRESSLY SET FORTH HEREIN, NSI INDUSTRIES MAKES OR GIVES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED. Except where prohibited by law, NSI Industries LLC will not be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.