# Safety Data Sheet
acc. to OSHA HCS

Date of issue: 01/13/2026 Revised On 01/13/2026

## 1 Identification

**Trade name:** **GLOSS GREEN ENAMEL**
**Other means of identification**

**Product code:** 0000160126
**Recommended use:** Paint and coatings application.
**Uses advised against:** Any that differs from the recommended use.
**Manufacturer/Supplier:**

Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178 USA
phone: 815-895-9101
www.seymourpaint.com

Seymour of Sycamore
3041 Dougall Avenue, Suite 503
Windsor, ONT N9E 1S3 CANADA
phone: 800-435-4482
www.seymourpaint.com

**Emergency telephone number:** 1-800-255-3924

## 2 Hazard(s) identification

**Classification of the substance or mixture**

| | | |
|---|---|---|
| Aerosols 1 | H222-H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |
| Eye irritation 2A | H319 | Causes serious eye irritation. |
| Carcinogenicity 2 | H351 | Suspected of causing cancer. Route of exposure: Inhalation. |
| Specific target organ toxicity (single exposure) 3 | H336 | May cause drowsiness or dizziness. |
| Specific target organ toxicity (repeated exposure) 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |

**Additional information:**
**GHS Hazard pictograms**

GHS02 GHS07 GHS08

**Signal word** Danger

**Hazard-determining components of labeling:**
Acetone
titanium dioxide
methyl isobutyl ketone

**Hazard statements**
Extremely flammable aerosol. Pressurized container: may burst if heated.
Causes serious eye irritation.
Suspected of causing cancer. Route of exposure: Inhalation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing fume/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Dispose of contents/container in accordance with local/regional/national/international regulations.

**Effects of chronic overexposure:**
May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**Classification according to (d)(1)(ii) of § 1910.1200**
The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

**Hazards not otherwise classified**
There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures**
**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

| | | |
|---|---|---|
| 67-64-1 | Acetone | 25-50% |
| 74-98-6 | propane | 15-25% |

(Contd. on page 2)

**Safety Data Sheet**
**acc. to OSHA HCS**

Date of issue: 01/13/2026 Revised On 01/13/2026

**Trade name: GLOSS GREEN ENAMEL**

(Contd. of page 1)

| | | |
|---|---|---|
| 110-19-0 | Isobutyl Acetate | 10-15% |
| 106-97-8 | n-butane | 5-10% |
| 108-65-6 | PM acetate | 1-5% |
| 108-10-1 | methyl isobutyl ketone | 1-5% |
| 107-87-9 | Methyl Propyl Ketone | 1-5% |
| 2807-30-9 | Glycol Ether EP | 1-5% |
| 13463-67-7 | titanium dioxide | 1-5% |

## 4 First-aid measures

**Description of first aid measures**
**After inhalation:** Supply fresh air; consult doctor in case of complaints.
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
**After swallowing:** Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:** Dizziness
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing media**
**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.
**Special hazards:** Can form explosive gas-air mixtures.
**Protective equipment for firefighters:** A respiratory protective device may be necessary.
**Additional information** Cool endangered receptacles with water spray.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.
**Environmental precautions:** Do not allow product to reach sewage systems or ground water.
**Methods and material for containment and cleaning up:** Ensure adequate ventilation.

## 7 Handling and storage

**Precautions for safe handling** Use only in well ventilated areas.
**Fire/explosion protection:** Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

**Conditions for safe storage:**
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Store locked up.

## 8 Exposure controls/personal protection

**Components with limit values that require monitoring at the workplace:** The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

| | |
|---|---|
| **67-64-1 Acetone** | |
| PEL | Long-term value: 2400 mg/m³, 1000 ppm |
| REL | Long-term value: 590 mg/m³, 250 ppm |
| TLV | Short-term value: 1187 mg/m³, 500 ppm<br>Long-term value: 594 mg/m³, 250 ppm<br>A4, BEI |
| **74-98-6 propane** | |
| PEL | Long-term value: 1800 mg/m³, 1000 ppm |
| REL | Long-term value: 1800 mg/m³, 1000 ppm |
| TLV | see Appendix F Minimal oxygen content ( D, EX) |
| **110-19-0 Isobutyl Acetate** | |
| PEL | Long-term value: 700 mg/m³, 150 ppm |
| REL | Long-term value: 700 mg/m³, 150 ppm |
| TLV | Short-term value: 712 mg/m³, 150 ppm<br>Long-term value: 238 mg/m³, 50 ppm |

(Contd. on page 3)

**Safety Data Sheet**
**acc. to OSHA HCS**

Date of issue: 01/13/2026 Revised On 01/13/2026

**Trade name: GLOSS GREEN ENAMEL**

(Contd. of page 2)

| | |
|---|---|
| **106-97-8 n-butane** | |
| REL | Long-term value: 1900 mg/m³, 800 ppm |
| TLV | Short-term value: 2370 mg/m³, 1000 ppm<br>(EX) |
| **108-65-6 PM acetate** | |
| WEEL | Long-term value: 50 ppm |
| **108-10-1 methyl isobutyl ketone** | |
| PEL | Long-term value: 410 mg/m³, 100 ppm |
| REL | Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 205 mg/m³, 50 ppm |
| TLV | Short-term value: 307 mg/m³, 75 ppm<br>Long-term value: 82 mg/m³, 20 ppm<br>BEI, A3 |
| **107-87-9 Methyl Propyl Ketone** | |
| PEL | Long-term value: 700 mg/m³, 200 ppm |
| REL | Long-term value: 530 mg/m³, 150 ppm |
| TLV | Short-term value: 529 mg/m³, 150 ppm |

| | |
|---|---|
| **Ingredients with biological limit values:** | |
| **67-64-1 Acetone** | |
| BEI | 25 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
| **108-10-1 methyl isobutyl ketone** | |
| BEI | 1 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MIBK |

**Exposure controls**

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

**General Information:**

| | |
|---|---|
| **Physical state** | Aerosol |
| **Odor:** | Aromatic |
| **Odor threshold:** | Not determined. |
| **Melting point/Melting range** | Undetermined. |
| **Boiling point:** | -110 °C (-166 °F) |
| **Flammability:** | Extremely flammable. |
| **Lower Explosion Limit:** | 1.7 Vol % |
| **Upper Explosion Limit:** | 10.9 Vol % |
| **Flash point:** | -19 °C (-2.2 °F) |
| **Decomposition temperature:** | Not determined. |
| **pH-value:** | Not determined. |
| **Viscosity:** | Not determined. |
| **Kinematic:** | Not determined. |
| **Dynamic:** | Not determined. |
| **Solubility:** | Not determined. |
| **Vapor pressure:** | 40 PSI 2750 hPa |
| **Vapor Pressure:** | 40 PSI, 2750 hPa |
| **Relative Density:** | Between 0.77 and 0.85 (Water equals 1.00) |
| **Vapor density** | Not determined. |
| **Particle characteristics** | Not applicable. |
| **Appearance:** | Aerosol. |
| **Ignition temperature:** | Product is not self-igniting. |
| **Danger of explosion:** | Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.<br>In use, may form flammable/explosive vapour-air mixture. |
| **Water:** | 0.0 % |
| **Evaporation rate** | Not applicable. |

(Contd. on page 4)

# Safety Data Sheet
acc. to OSHA HCS

Date of issue: 01/13/2026 Revised On 01/13/2026

**Trade name: GLOSS GREEN ENAMEL**

(Contd. of page 3)

**Partition coefficient: n-octonal/water:** Not determined.

## 10 Stability and reactivity

**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
**Possibility of hazardous reactions:** No dangerous reactions known.
**Conditions to avoid** No further relevant information available.
**Incompatible materials:** No further relevant information available.
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

**LD/LC50 values that are relevant for classification:**

| | | |
|---|---|---|
| **110-19-0 Isobutyl Acetate** | | |
| Oral | LD50 | 4,763 mg/kg (rabbit) |
| **108-65-6 PM acetate** | | |
| Oral | LD50 | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat) |
| **108-10-1 methyl isobutyl ketone** | | |
| Oral | LD50 | 2,100 mg/kg (rat) |
| Dermal | LD50 | 16,000 mg/kg (rab) |
| Inhalative | LC50/4 h | 11 mg/l (ATE) |
| | | 8.3-16.6 mg/l (rat) |
| **13463-67-7 titanium dioxide** | | |
| Oral | LD50 | >20,000 mg/kg (rat) |
| Dermal | LD50 | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat) |

**Skin effects:** No irritant effect.
**Eye effects:** Irritating effect.
**Sensitization:** No sensitizing effects known.
**Aspiration hazard**
**Interactive effects** No interactive effects between components are known.

| **IARC (International Agency for Research on Cancer)** | | |
|---|---|---|
| 108-10-1 | methyl isobutyl ketone | 2B |
| 13463-67-7 | titanium dioxide | 2B |

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**Alternative sources for toxicological information** No non-standard sources for toxicological information where used.

## 12 Ecological information

**Toxicity**
**Aquatic toxicity:** Hazardous for water, do not empty into drains.
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
**Bioaccumulative potential:** No further relevant information available.
**Mobility in soil:** No further relevant information available.
**Results of PBT and vPvB assessment**
**PBT:** Not applicable.
**vPvB:** Not applicable.
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
**Waste treatment methods**
**Recommendation:** Completely empty cans should be recycled.
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number** UN1950
**DOT** UN1950
UN1950

(Contd. on page 5)

# Safety Data Sheet
acc. to OSHA HCS

Date of issue: 01/13/2026 Revised On 01/13/2026

**Trade name: GLOSS GREEN ENAMEL**

(Contd. of page 4)

**UN proper shipping name:**
**DOT** AEROSOLS, flammable
**Transport hazard class(es):**
**Class** 2.1 Gases
**Marine pollutant:** No

**DOT**
**Packaging Group:** --
**Special precautions for user:** Warning: Gases
**EMS Number:** F-D,S-U

## 15 Regulatory information

**Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla**
**Toxic Substances Control Act (TSCA):** All ingredients are found on the inventory list of substances.
**Consumer Product Safety Comission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

| **Hazardous Air Pollutants** | |
|---|---|
| 108-10-1 | methyl isobutyl ketone |
| 1330-20-7 | xylene (mix) |
| 100-41-4 | ethyl benzene |
| 136-52-7 | cobalt bis(2-ethylhexanoate) |

| **California Proposition 65 chemicals known to cause cancer:** | |
|---|---|
| 108-10-1 | methyl isobutyl ketone |
| 13463-67-7 | titanium dioxide |
| 100-41-4 | ethyl benzene |

| **Prop 65 chemicals known to cause birth defects or reproductive harm:** | |
|---|---|
| 108-10-1 | methyl isobutyl ketone |

**CANADIAN ENVIRONMENTAL PROTECTION ACT:** All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

| **EPA:** | | |
|---|---|---|
| 67-64-1 | Acetone | I |
| 110-19-0 | Isobutyl Acetate | D |
| 108-10-1 | methyl isobutyl ketone | I |

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
**Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing fume/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves/protective clothing/eye protection/face protection.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Dispose of contents/container in accordance with local/regional/national/international regulations.
**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This product was manufactured in the U.S.A.
The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
**Contact:** Regulatory Affairs
**Date of previous version** 05/20/2025
**Date of preparation** 01/13/2026

**Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 6)

# Safety Data Sheet
**acc. to OSHA HCS**

Date of issue: 01/13/2026 Revised On 01/13/2026

**Trade name: GLOSS GREEN ENAMEL**

(Contd. of page 5)

PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Aerosols 1: Aerosols – Category 1
Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
Carcinogenicity 2: Carcinogenicity – Category 2
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2