Seymour of Sycamore

3041 Dougall Avenue, Suite 503

Printing date 01/03/2024 Revised On 01/03/2024

### 1 Identification of the substance and manufacturer

Trade name: **GLOSS WHITE** Product code: 0000011413

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:** 

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor. Eye Irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms







Signal word

Flammable liquid and vapor. **Hazard statements** Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

# 3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
64742-47-8	Mineral Spirits	15-25%	
13463-67-7	titanium dioxide	15-25%	
7727-43-7	barium sulfate	10-15%	
1330-20-7	xylene (mix)	1-5%	
111-76-2	Glycol Ether EB	0.2-1%	

# 4 First-aid measures

Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. After skin contact:

After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

No further relevant information available. effects:

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Special hazards: No further relevant information available.

Protective equipment for

firefighters: No special measures required.

# Safety Data Sheet

Printing date 01/03/2024 Revised On 01/03/2024

Trade name: GLOSS WHITE

(Contd. of page 1)

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Not required.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### 7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

# 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15\* 5\*\* mg/m³

\*total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction

Long-term value: 5\* mg/m³ \*inhalable fraction; E TLV (USA)

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, A4

111-76-2 Glycol Ether EB

PEL (USA) Long-term value: 240 mg/m³, 50 ppm

Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm

Skin

TLV (USA) Long-term value: 20 ppm

BEI, A3

#### Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

## 111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

**Hygienic protection:** 

Wash hands after use

Do not eat or drink while working.

Breathing equipment:

Not required.

Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

Eye protection:

#### 9 Physical and chemical properties

Appearance: Odor threshold: Liquid.

pH-value:

Not determined. Not determined.

Melting point/Melting range

Undetermined. 157 °C (314.6 °F)

Boiling point: Flash point:

43 °C (109.4 °F) Flammable.

Flammability (solid, gas): Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:

0.5 Vol %

(Contd. on page 3)

(Contd. of page 2)

# Safety Data Sheet

Printing date 01/03/2024 Revised On 01/03/2024

Trade name: GLOSS WHITE

**Upper Explosion Limit:** 6.5 Vol %

Vapor pressure: Not determined. Vapor density Not determined. Evaporation rate Not determined. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined

10 Stability and reactivity

Viscosity:

Conditions to avoid: No decomposition if used according to specifications.

Not determined.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

### 11 Toxicological information

LD/LC50 values that are relevant for classification:				
13463-67-7 titanium dioxide				
Oral	LD50	>20,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rbt)		
Inhalative	LC50/4 h	>6.82 mg/l (rat)		
1330-20-7 xylene (mix)				
Oral	LD50	8,700 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rbt)		
Inhalative LC50/4 h 6,350 mg/l (rat)				
111-76-2 Glycol Ether EB				
Oral	LD50	1,200 mg/kg (ATE)		
		1,480 mg/kg (rat)		
Dermal	LD50	400 mg/kg (rab)		
Inhalative	LC50/4 h	3 mg/l (ATE)		

Information on toxicological effects: No data available. Skin effects: No irritant effect. No irritating effect. Eye effects:

Sensitization: No sensitizing effects known.

# 12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

No further relevant information available. Bioaccumulative potential: Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

# 14 Transport information

**UN-Number** 

DOT UN1263 DOT Paint **1263 PAINT** ADR

Transport hazard class(es):

3 Flammable liquids Class

Special precautions for user: Warning: Flammable liquids

**EMS Number:** F-E,<u>S-E</u> Stowage Category Packaging Group: Ш

UN 1263 PAINT, 3, III UN "Model Regulation":

Safety Data Sheet

Printing date 01/03/2024 Revised On 01/03/2024

Trade name: GLOSS WHITE

(Contd. of page 3)

D, CBD(inh), NL(oral)

### 15 Regulatory information SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed. SARA Section 313 (Specific toxic chemical listings): 7727-43-7 barium sulfate 1330-20-7 xylene (mix) **Toxic Substances Control Act** (TSCA): Canadian Domestic Substances List All hazardous ingredients are found on the inventory list of substances. (DSL): All ingredients are listed or exempted. Consumer Product Safety This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. Comission (CPSC): California Proposition 65 chemicals known to cause cancer: 13463-67-7 titanium dioxide 100-41-4 ethyl benzene Prop 65 chemicals known to cause birth defects or reproductive harm: None of the ingredients is listed.

### 16 Other information

7727-43-7 barium sulfate

1330-20-7 xylene (mix)

EPA:

Contact: Regulatory Affairs