

Pan Style Mini-Brake[®]



Work. Perform. Outlast.
Limited Lifetime Warranty

Pan Style **MINI-BRAKE[®]**

Goes wherever you need to work.

For fabricating shop-quality pans and boxes, on the job, the Malco 48 in. (1.2 m) "Pan Style" Mini-Brake quickly breaks down and goes to work with you!

Initial assembly requires only a few metric wrenches, and / or adjustables, plus one supplied hex wrench. The fully assembled MB48B "Pan-Style" Mini-Brake is designed to be portable. At just under 100 pounds (45 kg), it may be carried comfortably by two people, or quickly separated into anvil and table components for one-person transport.




Create bending widths from 2 to 48 in. (50.8 mm-1.2 m)!



MB48B

Finger Plate Widths: • five 2 in. (50.8 mm) • six 3 in. (76.2 mm) • five 4 in. (101.6 mm)



When forming pans and boxes, remove & position finger plates as needed to span widths.

 **Choose a combination of fingers that will span the bending width as close as possible.** Adding space between fingers, when arranging combinations to accommodate fractional or uneven numbered pan or box side-width dimensions, will still produce an accurate bend. The anvil's clearance allows for a range of pan or box side-height dimensions from 1/2-inch (12.7 mm) to a maximum of 3-inches (76.2 mm).

Catalog Number	Description	Bend Angle	Max Bend Width	Min. Bend Width	Max Pan Height	Min. Pan Height	Min. Flange Net Wt.
MB48B	Mini-Brake	0 - 135°	48 in. (1.2 m)	2 in. (50.8 mm)	3 in. (76.2 mm)	.5 in. (12.7 mm)	99 lbs. (44.9 kg)
Options / Replacement Parts							
MBL	Leg Kit	—	—	—	—	—	—
MB48B2	Replacement Finger Plate for MB48B 2-in. (50.8 mm)	—	—	—	—	—	—
MB48B3	Replacement Finger Plate for MB48B 3-in. (76.2 mm)	—	—	—	—	—	—
MB48B4	Replacement Finger Plate for MB48B 4-in. (101.6 mm)	—	—	—	—	—	—
CAPACITIES							
MB48B	Material	Aluminum 18 ga.	Soft Copper 18 ga.	Zinc 18 ga.	Galvanized Steel 22 ga.	55% Al-Zn Mild Steel 22 ga.	
MB48B	in. (mm)	0.040 (1.02)	0.040 (1.02)	0.040 (1.02)	0.034 (0.86)	0.030 (0.76)	

Traditional Mini-Brake (MB48A) also available

www.malcotools.com

SL17831A