



ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	RSM-25200-B	BODY	ALUMINUM	1
2	SRB-208 THRU SRB-210	BUSHING	NEOPRENE	1
3	SOR-1-VNT	O-RING	BUNA-N	1
4	RSR-200-ND	NUT	ALUMINUM	1
5	RLM25-BR	LOCK NUT	BRASS, NICKLE PLATED	1
6	R-210-D	MESH	STAINLESS WIRE	1



CATALOG NUMBER	SEALING RANGE	BODY BORE
RSM-25208-E	.438 - .500	.800
RSM-25209-E	.500 - .562	.800
RSM-25210-E	.500 - .625	.800

REV.	DATE	CHANGE	UNLESS OTHERWISE SPECIFIED:	DRAWN	CHECKED	DATE	 <b>REMKE INDUSTRIES</b> 310 CHADDICK DR, WHEELING, IL. 60090	
A	8/14/13	DRAWING RELEASED	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1° ONE PLACE DECIMAL ± .015 TWO PLACE DECIMAL ± .010 THREE PLACE DECIMAL ± .005 INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL <b>ALUMINUM</b> FINISH DO NOT SCALE DRAWING	JCN		8/13	TITLE: <b>RSM-25208-25209-25210-E SERIES</b>	
							SIZE <b>A</b> DWG. NO. <b>RSM-25208-25209-25210-E ASSEMBLY</b>	
							SCALE: 1:1.1	SHEET 1 OF 1

5

4

3

2

1