

SLYDER

WIRE PULLING LUBE

All-in-one Wire Pulling Lubricant

Premium Performance

Slyder Clear Gel wire pulling lubricant is the premium choice to ensure maximum performance for faster, easier pulls. Safe to use on all types of wire and cable, Snyder is well-suited for electrical, telecommunications, and data applications.

Slyder's non-drip formula provides superior cling for ease of application and installation. Non-toxic, non-staining and non-flame propagating.



MADE IN
USA

UL
LISTED



Clear &
Colorless Gel



Easy
Clean-up



Will
Not Stain



Safe For All
Cable Types

Product Features

- Superior friction reduction and lower tension on cable pulls
- Clings evenly to provide superior friction reduction and ease of installation
- Compatible with all types of wire and cables, regardless of jacket or insulation material (rubber, neoprene, nylon, PVC, PE)
- Temperature range 30°F to 120°F (-1°C to 48°C)
- Clear, colorless, water-based formula, non-staining for easy cleanup
- No wax, grease or silicone; non-aromatic
- Safe, non-toxic, bio-degradable and eco-friendly



Product Specifications

Temperature Range	30°F to 120°F (-1* C to 48*C)
Temperature Stable	Yes
VOC Content	20 grams per Liter
Percent of of Solids	1.4% to 2.5%
pH	6.0 to 8.0
Acidity	None
Viscosity	170,000 cpd @ 40RPM
Aromatic Content	None
Flammability	No Flash point

Temperature Stability: Slyder Clear Gel demonstrates no physical phase-out after five freeze/thaw cycles or five-day exposure at 120°F (50°C).

Clean-Up: Slyder Clear Gel can be cleaned up using water.

Lubricity: Slyder Clear Gel has low 1.4 - 2.5% solids preventing cable “cement” and continued friction reduction. The residue is non-flammable.

Storage and Shelf Life: Slyder Clear Gel may be stored in standard warehouse conditions, away from light (UV) and ozone. Tightly reseal product after opening. Shelf life is one year after date of manufacture.

SKU	DESCRIPTION	PACKAGING	UPC
SCWL-1Q	Slyder Wire Pulling Lubricant Clear 1 QT	1 Quart Bottle	662381001368
SCWL-1G	Slyder Wire Pulling Lubricant Clear 1 Gal	1 Gallon Bucket	662381001375
SCWL-5G	Slyder Wire Pulling Lubricant Clear 5 Gal	5 Gallon Bucket	662381001382

Product Certifications

- UL/cUL listed 267
- CSA-C22.2 No. 249 Certified
- Tested to ASTM-D1693 UL Standard
- Passes IEEE 1210 and IEEE P1026IEEE standard tests

⚠ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

