

FEATURES:

1. Wire holes are stacked to minimize width. One-piece construction provides superior mechanical performance
2. Made from high strength 6061T-6 aluminum alloy
3. Options include a 350 mcm main lug and a high strength, glass-filled polyester mounting base for isolated mounting
4. Available in 12 to 42 wire holes (4-14 awg)

POLARIS®

PROGRAM:	SOLIDWORKS
UPDATED:	03/2024
SALES REV:	A
SIZE:	B (11x17)

NEUTRAL CONNECTORS: NEUTRAL 225A 600 VAC

CAT NO.	FIG NO.	NO. OF 4-14 AWG CIRCUITS	MAIN LUG SIZE	MOUNTING BASE	LENGTH	HEIGHT	WIDTH	STD. CTN. QTY.
1030	1	30	NONE	NO	5.260	0.875	1.500	1
1030M	2	30	350-6	NO	5.385	1.375	1.500	1
1030B	3	30	NONE	YES	5.260	2.250	2.250	1
1030MB	4	30	350 - 6	YES	5.385	2.750	2.250	1
1036	1	36	NONE	NO	6.324	0.875	1.500	1
1036M	2	36	350 - 6	NO	6.449	1.375	1.500	1
1036B	3	36	NONE	YES	6.324	2.250	2.250	1
1036MB	4	36	350 - 6	YES	6.449	2.750	2.250	1
1042	1	42	NONE	NO	7.388	0.875	1.500	1
1042M	2	42	350 - 6	NO	7.513	1.375	1.500	1
1042B	3	42	NONE	YES	7.388	2.250	2.250	1
1042MB	4	42	350 - 6	YES	7.513	2.750	2.250	1