

# Gutter Installation Tools



**Work. Perform. Outlast.**  
Limited Lifetime Warranty

## Snap Lock Punch

Ideal for crimping gutter end caps in place.



SL2R  
Not recommended  
for heavy sheet metal.

## 5 Blade Crimper

Produce a double crimp without deforming down-spout; walls stay square for a tight fitting, leakproof connection.



C4R

Slide adjustment for throat depth allows settings from 1/4 to 5/8 in. (6 to 16 mm) depth. Easy one-hand operation. Ideal for crimping gutter end caps in place. Also creates locking tabs in light sheet metals for joining metal sheets or inserting into rolled edge of utility trim. Formed metal cutting jaws and handles are made of hardened stampings. Rust-resistant nickel plate and black oxide finishes ensure long service life.

Use the Malco C4R Crimper to produce a crimp that downsizes corners of aluminum or steel downspout to create a male connection for joining downspout sections. The five blades of this versatile job-site hand tool produce a 1-1/4 inch (31.75 mm) long double crimp without deforming the downspout wall. This factory-like crimp ensures that the downspout wall stays square for a tight-fitting, leak-proof connection. The connection is also more self-supporting during installation. A handle closing stop maintains a consistent crimp profile. Hardened all-steel construction and a nickel chrome finish ensure long service life.

## Gutter Nail Driver



GND



## Single Crimper



SC2

**Works anywhere to attach gutter to fascia with ease.**

Use the Malco Gutter Nail Driver with hidden hangers and 8D galvanized nails to hang aluminum or steel gutters. A non-slip ergonomic grip provides multiple positions for grasping tool and working from above or below roof overhang. Durable 2-piece steel construction plus weather resistant zinc and nickel plating ensure long service life of this professional quality tool.

Light Duty tool without grips. Makes a single crimp for downsizing aluminum downspouts.

Catalog Number	Description	Throat Depth in. (mm)	Variable Leverage Ratio (High / Low) throughout stroke	Jaws	Length in. (mm)	Net Wt. oz. (g)
GND	Gutter Nail Driver	—	—	—	7-5/8 (194)	7 (199)
SL2R	Snap Lock Punch	1/4 to 5/8 (6.4 to 15.9)	—	—	8 (203)	16 (454)
C4R	5 Blade Crimper	1-1/4 (31.8)	7.1 to 1.0 - 9.8 to 1.0	Carbon Steel	9 (229)	16 (454)
SC2	Single Crimper	1-1/8 (28.6)	—	—	8 (203)	8 (227)
CAPACITIES						
	Material	Aluminum	Copper	Stainless Steel 26 Gauge	Galvanized Steel 24 Gauge	Mild Steel 24 Gauge
C4R	inches (mm)	0.035 (0.89)	0.023 (0.58)	0.018 (0.46)	0.028 (0.71)	0.024 (0.61)
Replacement Spring for Hand Tools						
5018	Fits C4R, SL2R					