

E-COAT PRIMERS



Seymour E-coats are designed to match the color and gloss of OEM factory primers. The high solids quick dry formula provides superior hide and coverage, saving you time and money. E-coat primers can be topcoated with both solvent and water borne automotive paints.

Suggested Uses:

Engine bay
 Support rails, crossmembers
 Trunk
 Vehicle floor

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Specific Gravity	0.82
Solids Content	16%
MIR value	Does not exceed 0.95
HAPs content	~14%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Acrylic
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To recoat	15 minutes
Hard Cure	8 hours

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: 40-55

*as measured on a 60 degree gloss meter

Available colors:

Color	Part Number	UPC Code
Black	16-1695	043281010009
Gray	16-1696	043281010016
Light Green	16-1697	043281010023
Olive	16-1698	043281010030
White	16-1699	043281010047

3-8-2022